



## CHEMICAL COMPATIBILITY CHART

A partial list of liquids that can be absorbed

Acetic Acid	Bromine	Diesel	Hydrazine, Anhydrous	Nitrobenzoic Acid	Sulfuric Acid
Acetic Anhydride	Butanol	Diethyl Ether	Hydrochloric Acid	Nitrotoluene	Tannic Acid
Acetone	Butyl Acetate	Diethylamine	Hydrogen Peroxide	Octane	Tetrachloroethylene
Acetonitrile	Butylamine	Dimethylformamide	Isobutyl Alcohol	Oleic Acid	Tetrahydrofuran
Acrolein	Butyric Acid	Dinitrobenzene	Isobutyric Acid	Paint	Thionyl Chloride
Acrylic Acid	Calcium Chloride Solution	Dioxane	Isopentyl Acetate	Perchloroethylene	Toluene
Acrylic Emulsions	Calcium Hydroxide Solution	Diisooctyl Phthalate	Isopropanol	Petroleum Ether	Transformer Oil
Acrylonitrile	Carbolic Acid	Ethanol	Isopropyl Acetate	Phenol	Transmission fluid
Allyl Alcohol	Carbon Disulfide	Ether	Isopropyl Alcohol	Phosphoric Acid	Trichloroethylene
Aminobenzoic Acid	Carbon Tetrachloride	Ethyl Acetate	Kerosene	Plating Solutions	Triethylamine
Ammonium Fluoride Solution	Castor Oil	Ethyl Alcohol	Ketones	Propanol	Triethylene Glycol
Ammonium Hydroxide	Chlorine Water	Ethyl Benzene	Linseed Oil	Propionic Acid	Turpentine
Amyl Acetate	Chloroacetic Acid	Ethyl Chloride	Lubricating Oil	Propyl Alcohol	Urine
Amyl Alcohol	Chlorobenzene	Ethyl Ether	Malathion	Propylene Glycol	Vinegar
Aniline	Chloroform	Ethyl Propionate	Methanol	Quinoline	Vinyl Acetate
Aqua Regia	Chlorosulfonic Acid	Ethylene Glycol	Methyl Chloride	Resorcinol Solution	Water
Auto coolant	Chromic Acid	Formic Acid	Methyl Ether	Salt Solutions (metallic)	Xylene
Aviation Fuel	Citric Acid Solution	Formaldehyde	Methyl Ethyl Ketone	Si <b>l</b> icone Oil	
Barium Chloride Solution	Clorox	Fuel Oil	Methyl Isobutyl Ketone	Silver Nitrate Solution	
Benzene	Cottonseed Oil	Gasoline	Methyl Propionate	Soap Solution (concentrated)	
Benzoic Acid	Cresol	Gear Oil	Mineral Oil	Sodium Bicarbonate Solution	
Benzonitrile	Cupric Chloride Solution	Glacial Acetic Acid	Mineral Spirits	Sodium Chloride Solution	
Benzoyl Chloride	Cyclohexane	Glycerol	Motor Oil	Sodium Hypochlorite	
Benzyl Alcohol	Detergents	Heptane	Naphtha	Sodium Nitrate Solution	
Boric Acid	Dichlorobenzene	Hexane	Nitric Acid	Stannic Chloride Solution	
Brake Fluid	Dichloromethane	Hydraulic Oil	Nitrobenzene	Sucrose Solution	

Do not use Floor-Dry<sup>tm</sup> or Solid-a-Sorb<sup>®</sup> to absorb hydrofluoric acid or concentrated sodium hydroxide solutions. Be advised that when using ANY absorbent that flammable materials, especially those that have a tendency to auto-ignite, may still burn or auto-ignite even after they are absorbed. Dispose of all absorbed product promptly, properly and in accordance with applicable laws.

