

DOOR CLOSERS

550 SERIES DUAL VALVE




FEATURES

- UL AND C-UL LISTED
- 5 YEAR GUARANTEE
- MEETS OR EXCEEDS REQUIREMENTS OR BMHA/ANSI 156.4 - GRADE 2
- IN COMPLIANCE WITH C.G.S.B. STANDARDS
- DUAL VALVE ADJUSTABLE (CLOSING & LATCHING SPEED)
- REVERSIBLE FOR BOTH RIGHT AND LEFT HANDED DOORS
- UNIVERSAL MOUNTING (REGULAR & PARALLEL BRACKETS INCLUDED)
- HIGH STRENGTH PRESSURE CAST ALUMINUM HOUSING
- FULL RACK AND PINION MECHANISM
- HIGH LUBRICITY AND LOW POUR POINT HIGH QUALITY HYDRAULIC FLUID
- LEAK PROOF "O" RINGS OIL SEAL


FOR PRODUCT SPECIFICATIONS CONTACT YOUR TAYMOR SALES ASSOCIATE

CONFORMS TO POSITIVE PRESSURE - STANDARD ULIOC AND UBC-7-2 (1977)


SIZE 2



SIZE 3



SIZE 4



	SIZE	MAXIMUM RECOMMENDED DOOR SIZE & WEIGHT	ALUMINUM	BRASS	CASE PACK
DOOR SIZE: DOORS SUBJECT TO STRONG WIND OR DRAFT CONDITIONS, OR ROUGH USAGE, REQUIRE THE NEXT SIZE CLOSER	2	36" x 84" [90cm x 210cm] 55-100 lbs/25 - 45 kg	13-552APAL	13-552APBR	6
	3	38" x 84" [95cm x 210cm] 88-144 lbs/40 - 64 kg	13-553APAL	13-553APBR	6
	4	42" x 96" [105cm x 240cm] 132-87 lbs/60 - 84 kg	13-554APAL	13-554APBR	6