



LINE VOLTAGE THERMOSTATS



201-8

HEAVY DUTY SPACE THERMOSTATS FOR HEATING AND COOLING

Designed for use in Garages, Factories, Warehouses and Similar Commercial and Industrial Installations

FEATURES

- Dust, moisture and vermin resistant heavy metal case.
- No leveling required – Mounts in any position.
- Quick response to temperature changes.
- Nickel plated element.
- Extra rugged switch mechanism with pure silver contacts.

SPECIFICATIONS

Dimensions $5\frac{3}{8}"$ H + $2\frac{1}{2}"$ coil x $2\frac{5}{16}"$ W x $2\frac{9}{16}"$ D
 Finish Grey color
 Agency U.L. listed and C.S.A. certified

Model Number	Range	Differential	Switch Action	Full Electrical Rating	Motor Rating (Full Load)		Valves and Relays	
					120 VAC	240 VAC	120 VAC	240 VAC
2A37-1	20 to 90°F (-7 to +32°C)	Adj. 3 to 20°F (2 to 11°C)	Open on Rise	FG See page 219	14.0A	7.0A	25.0A	22.0A
201-8	20 to 90°F (-7 to +32°C)	Adj. 3 to 20°F (2 to 11°C)	Close on Rise	FGH See page 219	16.0A	8.0A	25.0A	22.0A
201-20	-30 to +90°F (-34 to +32°C)	Adj. 4 to 20°F (2 to 11°C)	Close on Rise	FGH See page 219	16.0A	8.0A	25.0A	22.0A
227-8 ①	35 to 110°F (2 to +43°C)	Fixed 4°F (2°C)	SPDT	HH See page 219	7.4A	3.7A	7.4A	3.7A

① Coil on bottom, plastic coating on copper



201-16

HEAVY DUTY SPACE THERMOSTATS FOR HEATING AND COOLING

Designed for use in Garages, Factories, Warehouses and Similar Commercial and Industrial Installations

FEATURES

- Dust, moisture and vermin resistant heavy metal case.
- No leveling required – Mounts in any position.
- Quick response to temperature changes.
- Nickel plated element.
- Extra rugged switch mechanism with pure silver contacts.

SPECIFICATIONS

Dimensions 201 Model $5\frac{3}{8}"$ H + $2\frac{1}{2}"$ coil x $2\frac{5}{16}"$ W x $2\frac{9}{16}"$ D
 Finish Grey color
 Agency U.L. listed and C.S.A. certified

Model Number	Range	Differential	Switch Action	Full Electrical Rating	Motor Rating (Full Load)		Valves and Relays	
					120 VAC	240 VAC	120 VAC	240 VAC
201-16	35 to 110°F (2 to +43°C)	Fixed 3°F (1.5°C)	Close on Rise	FGH See page 219	16.0A	8.0A	25.0A	22.0A
201-196	35 to 110°F (2 to +43°C)	Fixed 3°F (1.5°C)	Close on Rise	FGH See page 219	16.0A	8.0A	25.0A	22.0A
259-6 ①	Low Speed: 35 to 110°F (2 to +43°C)	Fixed 3°F (1.5°C)	Close on Rise	HH See page 219	7.4A	3.7A	7.4A	3.7A
	High Speed: 35 to 110°F (2 to +43°C)	Fixed 4°F (2.2°C)	SPDT	HH See page 219	7.4A	3.7A	7.4A	3.7A
259-16	Low Speed: 35 to 110°F (2 to +43°C)	Fixed 3°F (1.5°C)	Close on Rise	HH See page 219	7.4A	3.7A	7.4A	3.7A
	High Speed: 35 to 110°F (2 to +43°C)	Fixed 4°F (2.2°C)	SPDT	HH See page 219	7.4A	3.7A	7.4A	3.7A

① 259-6 has plastic coated copper element