



90-T40F1



90-T40S3



90-T75C3

90-T40S1 THRU 90-T75C3 24 VOLT SECONDARY CLASS 2 TRANSFORMERS ENERGY LIMITING

For Industrial, Heating and Air Conditioning Controls Applications

FEATURES

- Color coded primary leads.
- Multi-mount styles available.

SPECIFICATIONS

Agency U.L. file number E33334
C.S.A. file number LR700786

MULTI-MOUNT (CLOSED CONSTRUCTION) UNIVERSAL MOUNTING WITH PLATE

Steveco		Mars Part No.	Jard Part No.	VA	Hz	Primary	Connections	Sec.	Connections
Model Number	Model Number								
90-T40M1	90-T40S1	50302	4011M	40	60	120V	Leads	24V	Leads
90-T40M2	90-T40S2	50303	4021M	40	50/60	208/240V	Leads	24V	Leads
90-T40M3	90-T40S3	50304	4031M	40	60	120/208/240V	Leads	24V	Leads
90-T50M3	90-T50S3	50314	5031M	50	60	120/208/240V	Leads	24V	Leads

90-TxxSx = screw terminal secondary

FOOT-MOUNT (OPEN CONSTRUCTION)

Steveco Model Number	Mars Part No.	Jard Part No.	VA	Hz	Primary	Connections	Sec.	Connections
90-T40F1	50352	4011F	40	60	120V	Leads	24V	Leads
90-T40F2	50353	4021F	40	50/60	208/240V	Leads	24V	Leads
90-T40F3	50354	4031F	40	60	120/208/240V	Leads	24V	Leads
90-T50F3	—	5031F	50	60	120/208/240V	Leads	24V	Leads

FOOT-MOUNT (MANUAL RESET, OPEN CONSTRUCTION)

Steveco Model Number	Mars Part No.	Jard Part No.	VA	Hz	Primary	Connections	Sec.	Connections
90-T50C3	50327	5041C	50	50/60	120/208/240V	Leads	24V	Leads
90-T60C3	50327	6041C	60	50/60	120/208/240V	Leads	24V	Leads
90-T75C3	50321	7541C	75	50/60	120/208/240V	Leads	24V	Leads

STEVECO TRANSFORMER LEAD COLOR CODING

Primary Side				Secondary Side	
Common	120V	208V	240V	Common	24V
Black	White	Blue	Red	Yellow	Yellow

WALL PLUG-IN

Isolation Step Down Transformer

FEATURES

- Sealed tamper and impact resistant case.
- Output termination is screw terminals.
- Non-polarized 120V plug-in blades.
- Trouble free maintenance.
- Isolated from power source.

SPECIFICATIONS

Dimensions, **5401A-1** 3"H x 2 1/2"W x 1 3/4"D
Dimensions, **5402A-1** 3"H x 2 3/4"W x 2 1/4"D
Output terminals #6-32 screws
Agency ratings C.S.A. and U.L. class 2



5401A-1

	Model Number	Primary	Secondary
NEW!	5401A-1	120VAC, 60 Hz, 0.14A	24VAC, 10VA
NEW!	5402A-1	120VAC, 60 Hz, 0.31A	24VAC, 25VA