



**G01A-332**

## 250/750 MILLIVOLT POWER GENERATOR

Provides Power for 250/750 Millivolt Self-Generation Control Systems

### FEATURES

- For replacement of similar screw-in type generators now in field or for use with type E31-12 pilot burner.
- G01A-332 has 36 inch armored cable leads with split-spade terminals.
- PG9 adapter included with each G01A-332. PG9 adapter also offered individually.

### PARTS AND ACCESSORIES

See end of this section for additional parts and accessories


- F145-1201 (replaces F92-0448) — Separate PG9 Adapter, available for use with the G01A-332 and G01A-502 Power Generators

#### 250 MV

Model Number	MV Output	Length	Fiberglass Cable Leads	Connector Type
G251A36S	250	36	X	A Terminal
G251F24S	250	24	X	F Spade Clip
G251F36S	250	36	X	F Spade Clip
G251R13V	250	13	X	R Bushing
G251R32V	250	32	X	R Bushing
G251R36S	250	36	X	R Bushing

#### 750 MV

Model Number	MV Output	Length	Fiberglass Cable Leads	Armored Cable Leads	PG9 Adapter	Connector Type
101934F32	750	32		X		F Spade Clip
101934F60	750	60		X		F Spade Clip
101934R32	750	32	X			R Bushing
G01A-332	750	36		X	X	F Spade Clip
G01A-512	750	36	X		X	F Spade Clip
G01A-132	750	36		X	X	F Spade Clip
G01A-518	750	18	X		X	F Spade Clip



**30A07-28**

**30A07-28**

## SAFETY PILOTS AND FLAME SENSORS

30A07 Series Safety Pilots used with Stud-Mount Mercury Flame Sensors

### FEATURES

- 30A07 pilots replace 3007 pilots.
- Two-flame pattern to match most field styles.
- Safety pilots include natural gas orifice.

#### SAFETY PILOTS

Model Number	Replaces Model Number
30A07-1	3007-1
30A07-28	3007-28

#### FLAME SENSORS

Model Number	Type Gas	Valve Type	Terminations	Cap Length	Comments
3046-5	Natural ③	①	Screw	42"	Recycling
30A46-5	Natural ③	②	Plug-in	42"	Recycling

① Screw terminals inside cover switch-case for use with any standard 24/120/240 VAC solenoid or diaphragm gas valve

② Plug-in switch-case for use with White-Rodgers "Silent Knight" (25G01 series) and "Cushioned Power" (25D46 series) solenoid valves page 52

③ Types 3046-5 and 30A46-5 can be used on LP gases only if an external means for automatic pilot gas shut-off is provided



**30A46-5**