

# PLUG FUSES

## SPECIAL PURPOSE



### PLUG fuses: G/GP/TD/GW/GTL/GT/GSL

Ferraz Shawmut Plug Fuses are for industrial and residential applications. Standard non-time delay fuses are for receptacle and lighting circuits. Standard time delay fuses are for motor loads.

For Canadian requirements, a type “P” fuse is used for non-motor loads and type “D” fuses are used for electric heating and cycling loads circuits. Both fuses have low melting-point temperature elements. Low-Temp time delay plug fuses have thermal sensitivity are also for cycling loads and motor circuits. Type “S” plug fuses are time delay and tamper-resistant.

#### Ratings

- 125V AC, 10kA I.R.
- 3 to 30 Amperes
- Choice of Edison Base, Types “P”, “D”, or “S”

#### Approvals

- UL Listed  
Guide JEFV, File E76208
- CSA Certified  
Class 142301, File 15525



### PLUG FUSES – Standard Fuse Ampere Ratings, Catalog Numbers

AMPERE RATING	CATALOG NUMBER						
	EDISON BASE						TYPE S
	Non-Time Delay UL	Non-Time Delay CSA	Time Delay UL	“P” Type Non- Time Delay CSA	Low-Temp Time-Delay UL	“D” Type Time Delay CSA	
3	GW3	G3	-	-	-	-	-
6	GW6	G6	-	-	-	-	-
10	GW10	G10	-	-	-	-	-
15	GW15	-	GTL15	GP15	GT15	TD15	GSL15
20	GW20	-	GTL20	GP20	GT20	TD20	GSL20
25	GW25	-	GTL25	GP25	GT25	TD25	GSL25
30	GW30	-	GTL30	GP30	GT30	TD30	GSL30

FR15 Rejection Rings available  
FRW Rejection removal tool available to remove FR15  
\*Must be used with an SAG adaptor to fit an Edison base fuse holder.



### TYPE S PLUG FUSE ADAPTORS

CAT. NO/RATING	FUSE RANGE - AMPS
SAG3-2/10	1-8/10 - 3-2/10
SAG6-1/4	3-1/2 - 6-1/4
SAG15	7 - 15
SAG20	20
SAG30	25 - 30

Type S adaptors screw into the Edison base and allow Type S fuses to be installed. Type S adaptors prevent the wrong ampere size fuse from being used.

**G**