

Mini-Rooter

ith 75 feet of 3/8" cable and a 1/3 hp motor, the Mini-Rooter clears lines from roof top to basement, including kitchen, bath and laundry drains. You can do heavier work in 4" lines when Mini-Rooter is equipped with 1/2" cable.

Quick.

You can remove the drum in seconds for more portability or to switch to a different diameter cable — with no mess and no lost time. A distributor tube inside the drum allows you to play the cable in and out without chucking and releasing the cable every few feet ... so you finish quicker. For small drain work, you can order your Mini-Rooter with a J-Drum or Dual Drum for handling smaller, more flexible cables.

Tough.

Rugged Flexicore® cables are unique. Rather than loosely sliding a core into a finished cable, we coil wire tightly around aircraft grade wire rope. This functional core greatly increases cable strength.

Convenient.

Compact design lets you take the Mini-Rooter almost anywhere. For long hauls, you can slip on a Mini-Rooter dolly and roll the machine to the job.

Some Mini-Rooter Safety Features

A foot pedal that uses air pressure to start and stop the machine without any electrical wiring between pedal and motor, and a ground fault circuit interrupter are standard equipment.



A variable speed power cable feed attachment makes feeding and retrieving the cable much easier. It quickly adjusts between 3/8" and 1/2" cables without the need for tools or additional parts. The power cable feed quickly attaches to all General Mini-Rooters.



The **Mini Rooter**™ SERIES

Mini-Rooter XP

Specifications:

Weight:

43 lbs. without cable (19.5 kg).

Dimensions:

18" deep x 12" wide x 19" high (46 cm x 30 cm x 48 cm).

Drum:

Capacity of 75 ft. of 3/8" or 1/2" Flexicore® wire rope center cable. Integral distributor tube. Quickly removable from frame.

J-Drum:

Capacity of 50 ft. of 1/4" or 5/16" Flexicore® cable.

Dual Drum:

Capacity of 25 ft. of 1/4" or 5/16" in inner drum. 50 ft. of 5/16" or 3/8" Flexicore® cable in outer drum.

1/3 hp. with forward-off-reverse switch, spring loaded mounting for proper belt tension. Load speed 165.

Belt Guard:

High impact plastic.

Foot Pedal:

Leaves operator's hands free to control cable. Uses air pressure, so there's no electrical contact between pedal and motor.

Power Cord:

10 ft. 3-wire in-line ground fault circuit interrupter.

Power Cable Feed:

(Optional) Drives and retracts cable at variable speed without reversing motor rotation.

Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.

Specifications:

Weight:

67 lbs. with power cable feed and without cable (30 kg).

Dimensions:

24" deep x 18" wide x 38" high, 24" high with handle folded down (61 cm x 46 cm x 96 cm).

Equipped with inner drum and distributor tube to prevent cable tangling under load. Quickly removable from frame.

Wheels:

8" semi-pneumatic tires with oilite bronze bushings.

Folding Handle:

Reduces truck storage space.

See Mini-Rooter Specifications for additional information.

Flexicore® Cable



Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.



Arrow head

Boring Gimlet

Cutter Set

See our complete catalog for additional optional cutters.





2" Side Cutter

Removable Drum

You can take the drum off the Mini-Rooter in seconds.



J-Drum and Dual Drum

With a J-Drum, you're ready for small drain work in seconds. An alternative, the Dual Drum holds two small dia. cables at the same time. You can switch from 1/4" to a 3/8" size without removing either one from the drum. Both will hold any Super-Vee cable.

Mini-Rooter Dolly

This lightweight but sturdy dolly is designed especially for the Mini-Rooter. It slips on or off in less than a minute and holds the machine securely.





1101 Thompson Avenue • McKees Rocks, PA 15136 USA 800-245-6200 or 412-771-6300 • Fax: 412-771-2771 Web Site: www.drainbrain.com

The toughest tools down the line.™

© General Wire Spring Co. 2009 C-MRS/0209