

## SPECIFICATION SHEET

## MODEL VX12000C CENTRAL VACUUM POWER UNIT



Designed for larger homes up to 12,000 square feet (1,114.8 m²) or consumers looking for the ultimate in features and air performance. This power unit has two specially designed 2-stage motors that delivers a whopping 1040 air watts of power. It's the most powerful in its class. The unique oval shape offers space saving advantages and efficient cyclonic filtration.

## **FEATURES**

- Internal sound suppression system makes it the quietest power unit in its class
- Progressive full lights tell the homeowner when to empty the debris pail
- · Easy access door for cyclonic filter maintenance
- Oversized debris pail handles make for quick and easy pail removal
- Large 7 gallon (26.5 litres) debris pail. Typically needs emptying only every 6 months!
- Dual vacuum air intakes allow for connecting to the tubing line from the right side, left side or both
- · Six foot (1.8 m) long power cord
- · cUL Listed

Limited Lifetime Warranty

## **SPECIFICATIONS**

Motors	.Two 2-Stage Universal Bypass	
Horsepower	.4.8 @ Full Open Orifice	
Amperes	.15	
Voltage	.240 VAC	
Airflow at 2" (50.8 mm) opening	230 CFM (108.5 L/s)	
Water Lift	.130" (3.3 m)	
Air Watts	.1040	
Switch on Power Unit Yes		
Utility Valve with Power UnitYes		
Recommended Circuit20 Amp		
Primary Filtration	Self-cleaning permanent HEPA Membrane Filter made with DuPont™ Teflon®	
Capacity	.7 Gallon (26.5 Litres)	
Secondary Filtration	.Screen	
cUL Listed	.Yes	
Housing	.Corrosion Resistant Flame Retardant Engineered Thermoplastic	
Power Unit Dimensions	.11.5" D x 17.5" W x 39" H	
(292 mm D x 445 mm W x 991 mm H)		



Broan-NuTone Canada Inc., 1140 Tristar Drive, Mississauga, Ontario, Canada L5T 1H9 (1-888-882-7626)

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date