WD Series


Tag: _____

Grease Interceptor

SPECIFICATION: Watts Drainage Products WD Series epoxy coated inside and outside fabricated steel grease interceptor with flow rating of 4 to 300 GPM and grease capacity of 8 to 600 lbs. Unit shall include one piece removable baffle assembly, code approved deep seal trap, secured and gasketed non slip cover, NH (MJ) (standard) inlet and outlet and internal flow control.

Ex. WD-104-T-FC





Interceptor Catalog Number	Grease Capacity Lbs	A Inlet & Outlet	B Base to Center	C Top to Center	D Length	E Width	F Height
WD-104	8	2"(51)	7-3/4"(197)	6"(152)	16"(406)	10"(254)	13-3/4"(349)
WD-107	14	2"(51)	8-1/2"(216)	6"(152)	18"(457)	13"(330)	14-1/2"(368)
WD-110	20	2"(51)	8-1/2"(216)	6"(152)	21-3/4"(552)	14"(356)	14-1/2"(368)
WD-115	30	2"(51)	10-1/2"(267)	6"(152)	22"(559)	15"(381)	16-1/2"(419)
WD-120	40	3"(76)	11-1/2"(192)	6"(152)	24"(610)	15-3/4"(400)	17-1/2"(445)
WD-125	50	3"(76)	12"(305)	6"(152)	26"(660)	16-1/2"(419)	18"(457)
WD-135	70	3"(76)	14"(356)	6"(152)	30"(762)	18"(457)	20"(508)
WD-150	100	4"(102)	16"(406)	6"(152)	32"(813)	22"(559)	22"(559)
WD-175	150	4"(102)	18-1/2"(470)	6"(152)	36"(914)	24"(610)	24-1/2"(622)
WD-210	200	4"(102)	29"(737)	10"(254)	40"(1016)	28"(711)	39"(991)
WD-215	300	4"(102)	39"(991)	10"(254)	40"(1016)	28"(711)	49"(1245)
WD-220	400	4"(102)	37"(940)	10"(254)	50"(1270)	34"(864)	47"(1194)
WD-225	500	4"(102)	39"(991)	10"(254)	50"(1270)	34"(864)	49"(1245)
WD-230	600	6"(150)	38"(965)	10"(254)	76"(1930)	45"(1143)	48"(1219)

Pipe Sizing (Select One)

Suffix	Description	
104	4 GPM	☐
107	7 GPM	☐
110	10 GPM	☐
115	15 GPM	☐
120	20 GPM	☐
125	25 GPM	☐
135	35 GPM	☐
150	50 GPM	☐
175	75 GPM	☐
210	100 GPM	☐
215	150 GPM	☐
220	200 GPM	☐
225	250 GPM	☐
230	300 GPM	☐

Options (Select One or More)

Suffix	Description	
-B	Sediment Bucket	☐
-DI	Dual Inlet	☐
-E	Extension* (Integral)	☐
-EB	Extension* (Bolt-on)	☐
-F	Flange	☐
-FC	Flange & Clamp Device	☐
-HDC	Heavy Duty Cover	☐
-O	Inlet & Outlet other than Standard Size	☐
-SS	Stainless Steel	☐
-MEFC	MJ External Flow Control	☐
-TEFC	Threaded External Flow Control	☐
-PDI-MEFC	PDI Label** with MJ External Flow Control	☐
-PDI-TEFC	PDI Label** with Threaded External Flow Control	☐

* For Overall "C" Dimension of 18", Order Integral Extension "-E18" or Bolt-on Extension "-EB12"

** PDI Certified Units Include External Flow Control. Note: Series WD-175 Not Yet Tested.

Optional Inlet/Outlet Sizes (When -O is selected above)

Suffix	Description	
-2	2"(51) Inlet/Outlet	☐
-3	3"(76) Inlet/Outlet	☐
-4	4"(102) Inlet/Outlet	☐
-6	6"(152) Inlet/Outlet***	☐

***Threaded Outlet or MEFC/TEFC External Flow Control Not Available

Job Name _____ Contractor _____

Job Location _____ Contractor's P.O. No. _____

Engineer _____ Representative _____

WATTS Drainage reserves the right to modify or change product design or construction without prior notice and without incurring any obligation to make similar changes and modifications to products previously or subsequently sold. See your WATTS Drainage representative for any clarification. Dimensions are subject to manufacturing tolerances.

CANADA: 5435 North Service Road, Burlington, ON, L7L 5H7 TEL: 905-332-6718 TOLL-FREE: 1-888-208-8927 Website: www.wattsdrainage.ca

© Watts Industries (Canada) Inc. 2008