BALLAST

TECHNICAL INFORMATION BULLETIN
ELECTRONIC CFL BALLAST
PROGRAM START

ORDERING INFORMATION

Order code: 31006
Description: E22150-347-SL GLB
Internal code: E22150-347-SL
UPC: 69549310063

GENERAL INFORMATION


Ballast type: Electronic
Starting method: Program Start
Lamp connection: Series
Input voltage: 347V
Input frequency: 60HZ
Status: Active
Safety approval: 31006STD

Lamp type	Number of lamps	Rated lamp watts	Min. start temp. (°F / °C)	Input current (A)	Input power (ANSI watts)	Ballast factor	Max THD %	Power factor	Max. lamp current crest factor	B.E.F.
32W TTT	2	32	-4/-20	0.20	68	0.85	10	0.99	1.7	1.25
26W TTT	2	26	-4/-20	0.18	60	0.92	10	0.99	1.7	1.53
36W TTL	2	36	-4/-20	0.19	64	0.79	10	0.99	1.7	1.23
24W TTL	2	24	-4/-20	0.16	55	0.90	10	0.99	1.7	1.64
F21T5	2	21	-4/-20	0.19	64	1.23	10	0.99	1.7	1.92
28W 2D	2	28	-4/-20	0.18	60	1.00	10	0.99	1.7	1.67
21W 2D	2	21	-4/-20	0.14	47	1.02	10	0.99	1.7	2.17
42W TTT	1	42	-4/-20	0.14	47	0.93	10	0.99	1.7	1.98
32W TTT	1	32	-4/-20	0.11	36	0.87	15	0.98	1.7	2.42
26W TTT	1	26	-4/-20	0.09	30	1.00	15	0.98	1.7	3.33
50W TTL	1	50	-4/-20	0.14	48	0.76	10	0.99	1.7	1.58
40W TTL	1	40	-4/-20	0.13	44	1.04	15	0.99	1.7	2.36
36W TTL	1	36	-4/-20	0.10	34	0.82	15	0.98	1.7	2.41
24W TTL	1	24	-4/-20	0.08	28	0.92	15	0.98	1.7	3.29
F21T5	1	21	-4/-20	0.10	32	1.25	15	0.98	1.7	3.91
28W 2D	1	28	-4/-20	0.10	32	1.10	15	0.98	1.7	3.44
21W 2D	1	21	-4/-20	0.08	26	1.15	20	0.98	1.7	4.42

BALLAST

TECHNICAL INFORMATION BULLETIN
ELECTRONIC CFL BALLAST
PROGRAM START

WIRING DIAGRAM




LEAD LENGTHS

Lead colour	in	cm
Black	4.72	12
White	4.72	12
Blue	6.69	17
Red	6.69	17
Yellow	6.69	17

BALLAST FEATURES

Length (L)	Width (W)	Height (H)	Mounting (M)
12.7 cm	6.3 cm	3 cm	11.2 cm
5 in	2.48 in	1.18 in	4.4 in



WARRANTY:
Ballast warranty of 5 years for electronic ballast 70 °C. Ballast warranty of 3 years for electronic ballast 90 °C.
For more information visit our website.

Data is based upon tests performed in a controlled environment and representative of relative performance.
Actual performance can vary depending on operating conditions.
Specifications are subject to change without notice.

STANDARD™
LEADERS IN LIGHTING

www.standardpro.com