



4700 W. 160th St.  
Cleveland, OH 44135  
1-800-321-9532  
WWW.OATEYCANADA.COM

## ALL PURPOSE LEAK DETECTOR



**TECHNICAL SPECIFICATION:** Oatey All Purpose Leak Detector is formulated to detect leaks on tubing, valves, cylinders pressure tanks or any other system under air, gas or oxygen pressure. Leak detector can be used at temperature range of -55° to 160° F.



### **COMMON APPLICATIONS**

Oatey All Purpose Leak Detector is recommend for use to detect leaks on pipelines, fittings, tanks, pressure vessels, valves and other hard surfaces.

Consult Oatey Technical Department for applications not specifically referenced above.

### **INGREDIENT (CAS Number)**

Ethylene Glycol (107-21-1)

### **PHYSICAL/CHEMICAL PROPERTIES**

Specific Gravity	1.039
Solubility in Water	Soluble
Boiling Point	238° F
Shelf Life	1 year from manufacture date
Appearance	Ice Blue Liquid
Odor	Citrus Fragrance

### **DIRECTIONS FOR USE**

Apply All Purpose Leak Detector to the connection to be checked. Watch for bubble clusters around connection. Large leaks will form large bubbles. Small leaks will form a white foam and may take several minutes to form. Do not dilute this product. Use directly from container. Remove excess All Purpose Leak Detector with water spray or wipe of with a damp rag.

### **PRECAUTIONS**

Read all cautions and directions carefully before using this product. Avoid contact with eyes and skin. Use with adequate ventilation. Wash thoroughly after handling. Keep container closed when not in use. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

Refer to material safety data sheet for more information.  
For emergency first aid help, call 1-303-623-5716 COLLECT.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT (lbs.)
30209	8 oz. Leak Detector with dauber	12	8
30211	16 oz. Leak Detector with trigger spray	12	17
30212	Gallon Leak Detector	4	39