

AGS COMPANY

P.O. Box 729 Muskegon, MI 49443 231-733-2101 Fax: 231-733-1784 info@agscompany.com

AIR COMPRESSOR OIL

DESCRIPTION:	The material covered by this specification is a non-detergent 30W air compressor oil, formulated to lubricate and protect air compressors operating in an ambient temperature range of 250 to 1200F. AGS AIR COMPRESSOR OIL is a superior lubricant containing an anti-wear agent, with corrosion and oxidation protection. Long, trouble-free service is assured under sustained high temperature and pressures. AGS AIR COMPRESSOR OIL has excedlent water separation characteristics, water separates readily from the oil for drain off during regular maintenance.

APPLICATION The material is formulated for optimal performance to reduce the carbonization, which can occur using multi-viscosityoils. AGS ZAIR COMPRESSOR OIL is recommended for all piston-type air compressors.

Packaging AGS AIR COMPRESSOR OIL is available in the following package sizes: CAT.NO. CONTAINER SIZES

AC-12 AC-17 AC-18 Ac-20 CONTAINER SIZES 12fl.oz bottle 32fl.oz. Bottle 1 gallon bottle 5 gallon pail

Properties **Physcial Form** Amber oil, liquid Specific Gravity, $60/60^{\circ}$ F (16/16°C) 0.8956 Density, lb/gal 7.457 Flash Point (C.O.C., ⁰F) 480 Viscosity @ 100⁰F 550 SUS SAE No. Crankcase Oil 30 SAE No. Gear Lubricant 80 Anti-Wear Package, Wt.% 0.09