



TECHNICAL DATA SHEET

LePAGE®

**Interior / Exterior
Wood Filler**

Henkel Canada Corporation

Professional and Consumer Adhesives
Mississauga, ON L5T 3A5
Phone 1-800-624-7767
Fax (440) 937-7067

www.henkel.com www.lepageproducts.com



DESCRIPTION

LePage® Interior/Exterior Wood Filler is a quality synthetic latex wood filler for cracks, holes and surface imperfections. It is a smooth, buttery paste that spreads and feathers easily and dries to match most light coloured wood. Interior/Exterior Wood Filler can be sanded, stained, painted, varnished, drilled, nailed and screwed. It will not shrink or crack up to an 18 mm (3/4") application. Interior/Exterior Wood Filler has a low odour and wet product can be easily cleaned with soap and water. It is weatherproof and mould and mildew resistant.

RECOMMENDED FOR:

Used for filling cracks, scratches and nail holes in wood, drywall and plaster. It can be used to level wood grain and chipped or gouged surfaces before painting.

NOT RECOMMENDED FOR:

- Continuous water immersion
- Outside application if rain is expected within 24 hours
- Tuck pointing applications on brick
- Use on floors, caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur
- Painted or primed surfaces
- Use as a skim coat

FEATURES & BENEFITS:

Feature	Benefits
Tan colour.....	Blends with most light coloured wood
Spreads smoothly.....	Requires only light sanding
Can be painted, stained or varnished.....	Blends with surroundings
Can be screwed or nailed.....	Won't crack or crumble from the wood
Contains mildewcide.....	Inhibits mould and mildew growth
Weatherproof.....	All-season durability

Item #	Package	Size
462071	Squeeze Tube	162 mL
462072	Plastic Tub	225 mL
462073	Plastic Tub	500 mL

DIRECTIONS

Tools Typically Required:

Utility knife, putty knife, 80 and 120 grit sandpaper.

Safety Precautions:

Keep out of reach of children.

Preparation:

Apply above 10°C (50°F). Surfaces must be clean, dry and free of grease, dust and other contaminants. Do not apply wood filler on painted or primed surfaces. Wood filler may be tinted using water-based tints or dry pigments. If using squeeze tube format, remove cap and cut nozzle at a 45° angle to desired size.

Application:

Using a putty knife, work filler into cracks and holes. If filling holes deeper than 18 mm (3/4"), apply filler in two or more applications. Allow each layer to dry before applying the next. For best results, overfill the final layer above the surface and sand level once dry. When sanding, start with 80 grit sandpaper followed by 120 grit. Sand in a circular motion to avoid grooving patch. Paint, stain or varnish once dry. When staining, the wood filler may absorb the stain differently than the surrounding wood. Test a small area first or experiment with a dried sample of wood filler until desired effect is achieved. For exterior applications, protect wood filler with paint, stain or varnish.

Clean-up:

Clean hands and tools immediately with soap and water. Cured filler may be carefully cut away with a sharp-edged tool or sanded.

STORAGE AND DISPOSAL

DAMAGED BY FREEZING. Store above freezing. Close the tube or lid tightly after each use. Product should not be washed down the drain. To dispose of unwanted product, scrape or squeeze out remaining material, allow to dry and discard with trash. Rinse and wipe container and place with plastics for recycling.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Refer to the Material Safety Data Sheet (MSDS) for further information

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

TECHNICAL DATA

Typical Uncured Physical Properties		Typical Application Properties	
<u>Colour:</u>	Tan	<u>Application Temperature:</u>	Apply above 10°C (50°F)
<u>Appearance:</u>	Paste	<u>Dry Time:</u>	A 2 mm (1/16") to 3 mm (1/8") depth dries in approximately 3 hours
<u>Odour:</u>	Minimal		An 18 mm (3/4") depth dries in approximately 24 hours.
<u>Base:</u>	Synthetic polymer		Dry time is dependent upon temperature, humidity and thickness of application.
<u>Specific Gravity:</u>	0.83		
<u>% Solids:</u>	66 %		
<u>pH:</u>	7.7		
<u>Viscosity:</u>	425 Mcps @ 1 rpm		
<u>Shelf Life:</u>	18 months from date of manufacture (Unopened)		
<u>Lot Code Explanation:</u>	YYDDD YY = Last two digits of year of manufacture DDD = Day of manufacture based on 365 days in a year For example: 09061 = 61 st day of 2009 = March 2, 2009		

Typical Cured Performance Properties

<u>Colour:</u>	Tan	<u>Service Temperature:</u>	-18°C (0°F) to 66°C (150°F)
----------------	-----	-----------------------------	-----------------------------