

Now with Wheels and Folding Handle



ired of carrying your drain cleaning machine to the jobsite? Now you don't have to. General's new Mini-Rooter Pro sports wheels to make it easier for you to transport it to and from the job, and a folding handle for compact storage in your truck.

The Mini-Rooter Pro clears drains from rooftop to basement, including kitchen, bath, and laundry drains. This tough little machine really saves time and trouble. For instance, you can remove the drum in seconds for more portability or to switch to a different diameter cable – with no mess and no lost time.

The drum carries up to 75 ft of 3/8" or 1/2" Flexicore[®] cable to clear 2", 3", and most 4" lines. For small drain work, you can order your Mini-Rooter Pro with a J-Drum for handling smaller, more flexible cables. An optional Power Cable Feed drives and retracts the cable at up to 16 feet per minute.

Flexicore® Cable

Flexicore[®] cables are made of heavy-gauge



wire coiled tightly around 49-strand aircraft type wire rope and heat treated. It has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870



Power Cable Feed

A variable speed Power Cable Feed (optional) drives and retracts the cable at up to 16 feet per minute. Quickly adjusts between 3/8" and 1/2" cables without the need for tools or additional parts. Swings out of the way to make drum changing as easy as ever. For smoother performance, switch to the XP drum with inner drum cage. **Catalog Number PO-MR**



Mini-Rooter Pro[™]

Folding handle

The handle is tall enough to make it easy to roll to the job, yet it can be quickly folded to take up less room in your truck.

Mini-Rooter Pro Cutter Set – Catalog # MRCS

	Cutter Name	Part Number	Application
	Arrow Head	AH	Starting Drill (Gets water flowing)
	1-1/2" U-Cutter	1-1/2UC	For cutting and scraping
\$	2" Side Cutter Blades	2SCB	For cutting and scraping
	Boring Gimlet	BG	For removing loose objects

Mini-Rooter Pro™ Units

MRP

Basic Unit: MR-200 Drum, 1/3 hp motor w/Reverse Switch, 10 ft. Power Cord w/GFCI, Water-Proof Air Foot Switch, Leather Gloves.

MRP-J

Basic Unit: Same as above, but with MR-250 J-Drum instead of MR-200 Drum.

MRP-A

Basic Unit, plus 50EM2 (50 ft. x 3/8") Cable, MRCS Cutter Set.

MRP-B

Basic Unit, plus 75EM2 (75 ft. x 3/8") Cable, MRCS Cutter Set.

MRP-C

Basic Unit, plus 50EM3 (50 ft. x 1/2") Cable, MRCS Cutter Set.

MRP-D

Basic Unit, plus 75EM3 (75 ft. x 1/2") Cable, MRCS Cutter Set.

PIPE CLEANERS

© General Wire Spring Co. 2012

Specifications:

Weight: 43 lbs. (19.5 kg) without cable.

- **Dimensions:** 20" D x 16" W x 38" H (20" H with handle folded) (51 cm x 41 cm x 96 cm - 51 cm)
- **Drum:** Capacity of 75 ft. x 3/8" or 1/2" Flexicore cable. Integral distributor tube. Quickly removable from frame.
- J-Drum: Capacity of 50 ft. of 1/4" or 5/16" Flexicore cable.
- Wheels: 6" semi-pneumatic tires.
- Folding Handle: Reduces storage space.
- Cutter Set: MRCS Cutter Set consists of Arrow head, Boring Gimlet, 1-1/2 U-Cutter, 2" Side Cutter Blades, Other cutters available.
- **Motor:** 1/3 hp, with forward-off-reverse switch, spring-loaded mounting for proper belt tension.

The toughest tools down the line.™

General Wire Spring Co. 1101 Thompson Avenue • McKees Rocks, PA 15136 USA 800-245-6200 or 412-771-6300 • Fax: 412-771-2771 www.drainbrain.com • e-mail: info@drainbrain.com



J-Drum

With a J-Drum (optional), you're ready for small drain work in seconds. Equipped with a collect chuck with tightening handle. Will hold any Super-Vee cable. **Catalog Number MR-250**



Removable Drum

You can take the drum off the Mini-Rooter Pro in seconds.

Built-in Dolly

Six inch semi-pneumatic wheels roll easily over rough terrain to and from the job.

Load Speed: 165 rpm.

Belt Guard: High impact plastic.

- **Power Cable Feed:** (Optional) Drives 3/8" and 1/2" cables. For smoother performance, switch to the XP drum with inner drum cage.
- Foot Pedal: Leaves operator's hands free to control cable. Uses air pressure, so there's no electrical contact between pedal an motor.
- **Power Cord:** 10 ft. 3-wire vinyl covered with molded plug. In-line ground fault circuit interrupter.
- Leather Gloves: With doublereinforced palm, for hand protection when guiding cable.

C-MRP-0812

