



REG-81J **8,000 BTUH**
Nominal

FEATURES

- Electronic controls with full feature remote, 24-hour on/off timer
- Energy saver mode, auto restart
- Four way adjustable air direction
- One degree temperature adjustment
- Designed for supplemental electric heat only, thermostat cycles heating element on and off

SPECIFICATIONS

Cooling Capacity BTUH	8,000
Approx. Sq. Ft. Cooling	300-350
EER	9.8
Heating Capacity BTUH (electric)	3,500
Power Supply	115V 60Hz
Humidity Removal Pts/Hr	1.48
Ventilation Control	No
Fan Only	Yes
Fan Speeds Cool/Heat/Fan	3/3/3
Air Delivery Max. CFM	278
dB Level (hi/med/low)	58/55/50
Amps Cooling	7.4
Amps Heating	11.6
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
In-Home Service	Yes
Shipping Weight (lbs.)	80
Dimensions (in.) Height	15 ⁹ / ₁₆
Width	23 ¹ / ₁₆
Depth	23 ⁷ / ₁₆



REG-123J **12,000 BTUH**
Nominal

FEATURES

- Electronic controls with full feature remote, 24-hour on/off timer
- Energy saver mode, auto restart
- Four way adjustable air direction
- One degree temperature adjustment
- Designed for supplemental electric heat only, thermostat cycles heating element on and off

SPECIFICATIONS

Cooling Capacity BTUH	11,600/12,000
Approx. Sq. Ft. Cooling	450-550
EER	9.8
Heating Capacity BTUH (electric)	8,500/11,000
Power Supply	208/230V 60Hz
Humidity Removal Pts/Hr	3.6
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Heat/Fan	3/3/3
Air Delivery Max. CFM	266
dB Level (hi/med/low)	58/56/53
Amps Cooling	5.5/5.5
Amps Heating	15.0/13.5
Maximum Fuse Size	20A
Power Cord	20A Tee NEMA 6-20P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
In-Home Service	Yes
Shipping Weight (lbs.)	88
Dimensions (in.) Height	15 ⁹ / ₁₆
Width	23 ¹ / ₁₆
Depth	23 ⁷ / ₁₆



REG-183J **18,000 BTUH**
Nominal

FEATURES

- Electronic controls with full feature remote, 24-hour on/off timer
- Energy saver mode, auto restart
- Four-way adjustable air direction
- One degree temperature adjustment
- Designed for supplemental electric heat only, thermostat cycles heating element on and off

SPECIFICATIONS

Cooling Capacity BTUH	18,200/18,500
Approx. Sq. Ft. Cooling	700-1000
EER	9.7
Heating Capacity BTUH (electric)	13,000/16,000
Power Supply	208/230V 60Hz
Humidity Removal Pts/Hr	3.8
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Heat/Fan	3/3/3
Air Delivery Max. CFM	459
dB Level (hi/med/low)	61/58/55
Amps Cooling	9.1/8.4
Amps Heating	22.0/20.0
Maximum Fuse Size	30A
Power Cord	30A Tandem NEMA 6-30P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
In-Home Service	Yes
Shipping Weight (lbs.)	127
Dimensions (in.) Height	17 ¹⁵ / ₁₆
Width	23 ⁵ / ₈
Depth	25 ⁷ / ₁₆

Cooling/Electric Heat

to 25,000 BTUH

Room Air Accessories



REG-183J-20A **18,000**
Nominal BTUH

FEATURES

- Electronic controls with full feature remote, 24-hour on/off timer
- Energy saver mode, auto restart
- Four-way adjustable air direction
- One degree temperature adjustment
- Designed for supplemental electric heat only, thermostat cycles heating element on and off

SPECIFICATIONS

Cooling Capacity BTUH	18,200/18,500
Approx. Sq. Ft. Cooling	700-1000
EER	9.7
Heating Capacity BTUH (electric)	9,100/11,200
Power Supply	208/230V 60Hz
Humidity Removal Pts/Hr	3.8
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Heat/Fan	3/3/3
Air Delivery Max. CFM	459
dB Level (hi/med/low)	61/58/55
Amps Cooling	9.1/8.4
Amps Heating	16.0/14.8
Maximum Fuse Size	20A
Power Cord	20A Tee NEMA 6-20P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
In-Home Service	Yes
Shipping Weight (lbs.)	127
Dimensions (in.) Height	17 ¹⁵ / ₁₆
Width	23 ⁵ / ₈
Depth	25 ⁷ / ₁₆



REG-253J **25,000 BTUH**
Nominal

FEATURES

- Electronic controls with full feature remote, 24-hour on/off timer
- Energy saver mode, auto restart
- Four-way adjustable air direction
- One degree temperature adjustment
- Designed for supplemental electric heat only, thermostat cycles heating element on and off

SPECIFICATIONS

Cooling Capacity BTUH	24,700/25,000
Approx. Sq. Ft. Cooling	1400-1500
EER	9.4
Heating Capacity BTUH (electric)	13,000/16,000
Power Supply	208/230V 60Hz
Humidity Removal Pts/Hr	5.7
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Heat/Fan	3/3/3
Air Delivery Max. CFM	541
dB Level (hi/med/low)	63/61/59
Amps Cooling	12.8/12.0
Amps Heating	22.5/20.0
Maximum Fuse Size	30A
Power Cord	30A Tandem NEMA 6-30P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
In-Home Service	Yes
Shipping Weight (lbs.)	142
Dimensions (in.) Height	18 ⁵ / ₈
Width	26 ¹ / ₂
Depth	25 ¹ / ₂



AS080 & AS160

Window Support Brackets

Easy-to-install brackets add a full measure of safety to window-mounted air conditioners. Manufactured from heavy gauge steel with a durable baked-on epoxy finish, the brackets have stainless steel hardware to resist weather damage. Unique bubble level helps ensure proper installation angle.

AS080—For room air conditioners up to 80 pounds

AS160—For room air conditioners up to 160 pounds

EA448F Wall Sleeve

For BG and BGE Series

Sleeve is manufactured of G-90 steel and powder coated for durability and corrosion resistance; color matches unit color. The sleeve utilizes the aluminum back grille of the BG/BGE units, and front gaskets eliminate air see page.

IMPORTANT: Always wait to cut a hole in structure until unit arrives and dimensions can be verified.

EA448F—Wall Sleeve (inches)
15¹⁷/₃₂" H x 25⁷/₈" W x 16²³/₃₂" D