Flexible Grey Vinyl Ducting

GFD Series



Applications

Dundas Jafine Flexible Two Ply Grey Vinyl Ducting can be used for a number of applications including: Heating, Air Conditioning and Exhausting.

Warranty

Dundas Jafine Flexible Two Ply Grey Vinyl Ducting is warranted to be free from defects in workmanship and material for one year from date of purchase.

Code Compliance

Dundas Jafine recommends that you check with the local code body, having jurisdiction in your area, to determine applicable codes.

Note

NOT RECOMMENDED FOR DRYER VENTING

Air Connector

This product consists of a 2-ply grey PVC film encapsulating a high density, corrosion resistant wire helix, forming an air tight, easy to use, quality air connector. It is ideal for use in general purpose exhaust applications including bathroom fans and furnace mounted humidifer units. The product comes in conveniently boxed 25 foot lengths, compressed for easy shipping and handling.

Features

- Totally flexible
- General purpose use

Benefits

- Easy to install
- Can be used in many exhaust applications

Flexible Grey Vinyl Ducting (GFD Series)

Performance Data

Static Pressure - positive: 10 in. WC

Static Pressure - negative: 1 in. WC

Maximum Velocity: 4000 FPM

Temperature Range: -10°F to 160°F

Accessories

For proper installation use Dundas Jafine Adjustable Plastic Clamps.

These are ideal for use with flexible ducting, featuring a quick release, self locking clasp. Plastic clamps fit all 3" - 6" applications.



Adjustable Plastic Clamps

Product Range

Diame	eters (ir	nche	s)				
4	5	6	8				
Standard Length (feet) 25							
Product Codes							
GFI	D425	(9FD525	GFD625	GFD825		

^{*} Note: All products are sold in bulk master packs.