


Open - 3000 RPM - Single / Double Shaft

Sleeve & Ball Bearing - Shaded Pole & P.S.C. - 115 Volts



Single Shaft

Part #	Amps.	H.P.	Rotation	Shaft	Body	Feature	Comment	Fig.
R305	0.85	1/60	C.W.	1.5"x1/4"	2.30	Cord & plug, 2800 RPM	Nutone	1
R307	1.10	1/30	C.C.W.	1.3"x1/4"	3.30	Stud mounting	Keeprite	2
R312	1.20	1/12	C.C.W.	4.0"x5/16"	4.63	P.S.C (4/370), Internal Fan, Ball Bearing, 3250 RPM	Engineered Air 101322	3
R334	2.30	1/15	C.C.W.	1.5"x1/4"	4.25	Internal Fan	Torin/Clare	4



Double Shaft

Part #	Amps.	H.P.	Rotation	Shaft	Body	Feature	Comment	Fig.
R413	0.95	1/35	C.C.W.	2.3"x1/4"x2.5"	3.00	Int.Fan, cord & plug	Gen. Replacement	1
R445	1.10	1/35	C.W.	1.5"x1/4"x1.5"	2.80	75" cord & plug	Gen. Replacement	1

Totally Enclosed - 3000 RPM - Single / Double Shaft

Sleeve & Ball Bearing - Shaded Pole & P.S.C. - 115 Volts



Single Shaft

Part #	Amps	HP	Rot	Shaft	Body	Features	Comment	Fig.
R90402	0.75	1/60	CCW	1.73"x1/4"	2.36	4 studs front & rear	D402, 40402	1
R90616	0.75	1/70	CW	0.96"x1/4"	2.28	Cord & plug	82500	1
R214	0.76	1/50	C.W.	1.5"x1/4"	2.80	2700 RPM	Nutone	2
R233	0.84	1/45	C.C.W.	1.8"x1/4"	2.50	2 Speed Plug	Nutone	4
R200	1.00	1/50	C.C.W.	1.2"x1/4"	2.60	2 Speed Plug	Miami-Carey	3



Double Shaft

Part #	Amps.	H.P.	Rotation	Shaft	Body	Feature	Comment	Fig.
R412	0.55	1/75	C.C.W.	2.3"x1/4"x2.3"	2.40	22" cord & plug	Gen. Replacement	1
R425	1.00	1/40	C.W.	2.5"x1/4"x2.5"	2.60	4 studs front & back, two speed	Gen. Replacement	1