# TECHNICAL INFORMATION BULLETIN MAGNETIC CFL BALLAST PRE HEAT

### **ORDERING INFORMATION**

Order code: Description: Internal code: UPC:


56610 1l FC8T9/PH/SS/120V V2 e: SSN2PWS 69549566101

#### **GENERAL INFORMATION**


Ballast type:	Magnetic
Starting method:	Preheat Start
Lamp connection:	
Input voltage:	120Vac +5% -10%
Frequency:	60HZ
Class:	Р
Туре:	1 outdoor
Sound rated:	А

Lamp type	Number of lamps	Rated lamp watts	Min. start temp. (°F / °C)	Input watts (W)	Input current (A)	Ballast factor	B.E.F.	Power factor	THD %	Lamp crest factor
FC6T9	1	20	50/10	20	0.35	0.35	3.95	0.458	20	1.68
FC8T9	1	19	50/10	19	0.27	0.27	4.16	0.586	15	1.58

## WIRING DIAGRAM



BALLAST FEATURES						
Unit	Μ	W	L	н		
INCHES	2.75	1.89	3.10	1.42		
mm	69.85	40.07	78.74	36.07		



LEAD LENGTHS							
	Black	White	Red	Blue	Yellow		
INCHES	12	12	9	9	9		
mm	304.8	304.8	228.6	228.6	228.6		

#### WARRANTY:

Ballast warranty of 2 years for electromagnetic ballasts. Ballast warranty of 3 years for energy saving electromagnetic ballasts. For more information visit our website.



Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



www.standardpro.com