



Pulse Start

Applications

- Parking garage
- Security lighting
- Retail lighting
- Airport lighting
- Residential roadways
- Canopy lighting
- Lowbay industrial lighting
- Site lighting

ED17



Dia. = 2 1/2 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/8 in. (86 mm)

ED17



Dia. = 2 1/2 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/8 in. (86 mm)

EDX17



Dia. = 2 1/2 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/8 in. (86 mm)

EDX17



Dia. = 2 1/2 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/8 in. (86 mm)

ED28



Dia. = 3 1/2 in. (89 mm)
MOL = 8 5/8 in. (211 mm)
LCL = 5 in. (127 mm)

ED28



Dia. = 3 1/2 in. (89 mm)
MOL = 8 5/8 in. (211 mm)
LCL = 5 in. (127 mm)

O = Open rated for indoor fixtures E = Enclosed rated

Order code	Description	Shape	Base	ANSI code	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Burn pos.	Finish	Luminaire	Case qty	Figure
------------	-------------	-------	------	-----------	------------------	-----	--------------------	---------------------	------------------	-----------	--------	-----------	----------	--------

150 watts

58025	MH150W/U/PS/740 STD	ED17	E26	M102/E	4 000	65	15 000	14 000	10 500	U	Clear	E	12	A
58018	MH150W/C/U/PS/737 STD	ED17	E26	M102/E	3 700	70	15 000	13 300	10 000	U	Coated	E	12	B
58053	MP150W/U/UVS/PS/740 STD	EDX17	E26	M102/O	4 000	65	15 000	13 300	10 000	U	Clear	O	12	C
58054	MP150W/C/U/UVS/PS/737 STD	EDX17	E26	M102/O	3 700	70	15 000	12 600	9 500	U	Coated	O	12	D
58038	MH150W/U/ED28/PS/740 STD	ED28	E39	M102/E	4 000	68	15 000	14 000	10 500	U	Clear	E	12	E
58057	MP150W/C/U/ED28/UVS/PS/737 STD	ED28	EX39	M102/O	3 700	70	15 000	12 600	9 500	U	Coated	O	12	G

175 watts

58044	MS175W/BU/MED/PS/740 STD	ED17	E26	M152/E	4 000	65	15 000	17 500	14 000	BU±15°	Clear	E	12	A
59144	MS175W/C/BU/MED/PS/737 STD	ED17	E26	M152/E	3 700	70	15 000	16 600	13 300	BU±15°	Coated	E	12	B
57986	MS175W/BU/PS/740 STD	ED28	E39	M152/E	4 000	65	15 000	17 500	14 000	BU±15°	Clear	E	12	E
57984	MS175W/C/BU/PS/737 STD	ED28	E39	M152/E	3 700	70	15 000	16 600	13 300	BU±15°	Coated	E	12	F

200 watts

57976	MS200W/BU/MED/PS/740 STD	ED17	E26	M136/E	4 000	68	12 000	21 000	16 800	BU±15°	Clear	E	12	A
57967	MS200W/V/PS/740 STD	ED28	E39	M136/E	4 000	68	15 000	21 000	16 800	BU±15°	Clear	E	12	E
57987	MS200W/C/V/PS/737 STD	ED28	E39	M136/E	3 700	70	20 000	20 000	16 000	BU±15°	Coated	E	12	F