

TECHNICAL INFORMATION BULLETIN

CIRCLINE

Ordering Information

Order code: 58984
Description: FC6T9/CW/RS/4P/STD
UPC: 69549589841
Case quantity:



Performance Data

Initial lumens (lm): 890
Mean lumens (lm): 710
Nominal efficiency (lm/W): 45
Wattage (W): 20
Colour temperature (K): 4 100
CRI: 82
Average life (hrs): 10 000

¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

Lamp Characteristics

Shape: T9 Circline
Base: G10q-4
Diameter: 1 3/16 in. (30 mm)
Nominal length: 6 1/2 in. (165 mm)
Starting method: Rapid Start
TCLP compliant: Yes
Phosphor composition: Triphosphor
Cathode guard: Yes
Nominal lamp operating frequency (Hz): 60

² Minimum starting temperature (°C): -10


Benefits

One system Lamp/Ballast Warranty.
Extended lamp warranty from 2 to 3 years and ballast warranty from 3 to 5 years.



² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T9 Instant Start ballast.

Dimensions



A Max
Inner diameter
from base to tube

B Min/B Max
Inner diameter from
tube to tube
3.99 in./ 4.23 in.
101.5 mm/ 107.5 mm

C Max
Outer overall diameter from
base to tube

20 watts

4.23 in.
107.5 mm

6.50 in./ 165.8 mm

Spectral distribution

