

TECHNICAL INFORMATION BULLETIN T8 3 FEET 800 SERIES

Ordering Information

Order code: 10003
Description: F25T8/41K/8/RS/G13/STD ESV
UPC: 69549100039
Case quantity: 25



Performance Data

Initial lumens (lm): 2 225
Mean lumens (lm): 2 140
Nominal efficiency (lm/W): 89
Wattage (W): 25
Colour temperature (K): 4 100
CRI: 85
Average life (hrs): 24 000

1 The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

Lamp Characteristics

Shape: T8
Base: Med Bipin
Diameter: 1 in. (26 mm)
Nominal length: 36 in. (915 mm)
Starting method: Rapid Start (RS)
TCLP compliant: Yes
Phosphor composition: Triphosphor
Cathode guard: Yes
Nominal lamp operating frequency (Hz): 60

² Minimum starting temperature (°C): -10


Benefits

One system Lamp/Ballast Warranty.
Extended lamp warranty from 2 to 3 years and ballast warranty from 3 to 5 years.




2 The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T8 Instant Start ballast.

Dimensions



	A Max Base face to base face	B Min/B Max Base face to end of opposite face pin	C Max End of base pin to the end of opposite end
F25T8	35.22 in. 894.6 mm	35.40 in. / 35.50 in. 899.2 mm / 901.7 mm	35.78 in. 908.8 mm

Spectral distribution



For more information on our complete product line visit us at www.standardpro.com