



Benefits

STANDARD offers a wide variety of fluorescent lamps for specialized applications.



Specialty - Preheat Start

Order code	Description	Watts (W)	Shape	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Nominal length (in.) (mm)	Diameter (in.) (mm)	Efficacy (lm/W)	Case Qty
------------	-------------	--------------	-------	------	---------------------	-----	-----------------------	------------------------	------------------------------	------------------------	--------------------	----------

Appliance (For use with starters)

10506	F18T8/CW/APL/24/PH/G13/STD	18	T8	Med Bipin	4 100	62	7 500	1 225	24 610	1 26	82	100
10507	F16T8/CW/APL/26/PH/G13/STD	16	T8	Med Bipin	4 100	62	7 500	1 275	26 660	1 26	80	48
10508	F17T8/CW/APL/28/PH/G13/STD	17	T8	Med Bipin	4 100	62	7 500	1 350	28 711	1 26	79	100
10509	F18T8/CW/APL/30/PH/G13/STD	18	T8	Med Bipin	4 100	62	7 500	1 400	30 762	1 26	78	100

Specialty - Rapid Start

Order code	Description	Watts (W)	Shape	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Nominal length (in.) (mm)	Diameter (in.) (mm)	Efficacy (lm/W)	Case Qty
------------	-------------	--------------	-------	------	---------------------	-----	-----------------------	------------------------	------------------------------	------------------------	--------------------	----------

Black Light

51177	F32T8/BL/RS/G13/STD	32	T8	Med Bipin	N/A	N/A	20 000	N/A	48 1 220	1 26	N/A	25
51173	F32T8/BLB/RS/G13/STD	32	T8	Med Bipin	N/A	N/A	20 000	N/A	48 1 220	1 26	N/A	25

Colour

10624	F16T4/BLUE/475mm/G5/STD	16	T4	Med Bipin	Blue	N/A	3 000	N/A	19 475	1/2 13	N/A	200
10625	F20T4/RED/520mm/G5/STD	20	T4	Med Bipin	Red	N/A	3 000	N/A	20 520	1/2 13	N/A	200
51171	F32T8/GLD/RS/G13/STD	32	T8	Med Bipin	Gold	N/A	20 000	1 450	48 1 220	1 26	45	25

CRI 90+

51172	F32T8/50K/9/RS/G13/STD	32	T8	Med Bipin	5 000	90	24 000	2 300	48 1 220	1 26	72	25
51174	F32T8/FS/RS/G13/STD	32	T8	Med Bipin	5 700	92	24 000	2 300	48 1 220	1 26	72	25
51170	F32T8/50K/9/RS/G13/STD ESV	32	T8	Med Bipin	5 000	98	24 000	2 300	48 1 220	1 26	72	25

Metric (Designed to fit metric type fixtures)

10496	F32T8/35K/8/RS/G13/METRIC/STD	32	T8	Med Bipin	3 500	85	24 000	2 900	46 1 160	1 26	91	25
10497	F32T8/41K/8/RS/G13/METRIC/STD	32	T8	Med Bipin	4 100	85	24 000	2 900	46 1 160	1 26	91	25
10498	F32T8/FS/RS/G13/METRIC/STD	32	T8	Med Bipin	5 800	90	24 000	2 500	46 1 160	1 26	78	25

Plant Light

51176	F32T8/PLA/RS/G13/STD	32	T8	Med Bipin	N/A	N/A	20 000	1 400	48 1 220	1 26	44	25
-------	----------------------	----	----	-----------	-----	-----	--------	-------	----------	------	----	----

RBG

51175	F32T8/RS/G13/STD RBG	32	T8	Med Bipin	N/A	N/A	20 000	1 650	48 1 220	1 26	52	25
10001	F40T10/RS/G13/STD RBG	40	T10	Med Bipin	N/A	N/A	20 000	3 900	48 1 220	1 1/4 32	N/A	25

Order code	Description	Base	Colour temp. (K)	CRI	Rated life on IS ¹ ballast 3h / 12h	Rated life on PRS ¹ ballast 3h / 12h	Initial lumens (lm)	Mean lumens (lm)	Nominal length in. mm	Nominal diameter in. mm	Efficacy (lm/W)	Case qty
(at 25 °C) (at 5 °C) (at 5 °C)												

Cold Start - 32 watts

59244	F32T8/41K/8/RS/G13/ COLD START/STD	Med Bipin	4 100	85	24000 30000	30000 36000	2 550 2 700	2 565	47.24 1 200	1.50 38	84	25
-------	---------------------------------------	-----------	-------	----	----------------	----------------	-------------	-------	-------------	---------	----	----

Order code	Description	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length in. mm	Nominal diameter in. mm	Efficacy (lm/W)	Case qty
(at 25 °C) (at 5 °C) (at 5 °C)											

Cold Start - 54 watts

59243	F54T5/41K/8/HO/PS/G5/ COLD START/STD	Min Bipin	4 100	85	24000	3 900 4 900	4 655	45.23 1 149	.63 26	91	25
-------	---	-----------	-------	----	-------	-------------	-------	-------------	--------	----	----