

**ES SHAPED LAMPS** with a GU10 base also known as GU10 are increasingly used in decorative fixtures. Their line voltage transformer free operation is highly appreciated in general lighting.

ES lamps are also offered as specialty items with additional features.

All GU10 based lamps are fitted with a lens that filters UV rays.



ES16 (GU10)



MOL = 2 1/2 in. (55 mm)  
Dia. = 2 in. (51 mm)

ES16 (GU10)  
Neodymium



MOL = 2 1/2 in. (58 mm)  
Dia. = 2 in. (51 mm)

ES16 (GU10)  
Uni-Frost



MOL = 2 1/2 in. (55 mm)  
Dia. = 2 in. (51 mm)

ES16 (GU10)  
ICE



MOL = 2 1/2 in. (55 mm)  
Dia. = 2 in. (51 mm)

Order code	Description	Watts (W)	Base	Volts (V)	Colour temp. (K)	Beam angle (°)	Beam spread	CBCP (cd)	Average life (hrs)	Initial lumens (lm)	Case qty
<b>ES16</b>											
55034	H20GU10/NFL/CG/2.5M/120V/STD	20	GU10	120	2 800	25	Narrow Flood	500	2 500	120	100
55033	H35GU10/NFL/CG/2.5M/120V/STD	35	GU10	120	2 800	25	Narrow Flood	1 000	2 500	280	100
10437	H50GU10/NFL/CG/2.5M/120V/STD	50	GU10	120	2 800	25	Narrow Flood	1 400	2 500	500	100
55035	H50GU10/NFL/2M/CG/120V/ HS	50	GU10	120	2 800	25	Narrow Flood	1 400	2 000	N/A	15
10438	H50GU10/NFL/CG/3M/130V/STD	50	GU10	130	2 800	25	Narrow Flood	1 400	3 000	375	100
<b>ES16 Neodymium</b>											
60872	H50ES16/FL/N/CG/3M/GU10/130V/STD	50	GU10	130	Neodymium	35	Flood	1 800	3 000	410	120
<b>ES16 Uni-Frost</b>											
57212	H35GU10/CG/2.5M/120V/STD UFR	35	GU10	120	2 800	N/A	N/A	N/A	2 500	330	100
57213	H50GU10/CG/2.5M/120V/STD UFR	50	GU10	120	2 800	N/A	N/A	N/A	2 500	520	200
57801	H50GU10/CG/3M/130V/STD UFR	50	GU10	130	2 800	N/A	N/A	N/A	3 000	390	200
<b>ES16 ICE</b>											
55052	H20GU10/CG/2.5M/120V/STD ICE	20	GU10	120	2 800	40	Flood	300	2 500	130	100
55051	H35GU10/CG/2.5M/120V/STD ICE	35	GU10	120	2 800	40	Flood	600	2 500	280	100
55038	H50GU10/CG/2.5M/120V/STD ICE	50	GU10	120	2 800	40	Flood	840	2 500	500	100
55037	H50GU10/CG/3M/130V/STD ICE	50	GU10	130	2 800	40	Flood	840	3 000	375	100