



Features

- Longer life
- Uses less energy
- Brighter than conventional lamps
- Available in a wide variety of shapes, colours, sizes and wattages

Applications

- Residential
- Retail stores
- Track lighting
- Jewelry boutiques
- Wall washing

ES16



MOL = 2 1/2 in. (55 mm)
Dia. = 2 in. (51 mm)

J



MOL = 3 1/4 in. (79 mm)
Dia. = 1 1/2 in. (10 mm)

JD E11 base



MOL = 2 7/16 in. (62 mm)
Dia. = 1 1/2 in. (10 mm)

JD G9 base



MOL = 1 21/32 in. (42 mm)
Dia. = 15/32 in. (12 mm)

JC



MOL = 1 7/16 in. (31 mm)
Dia. = 11/16 in. (9 mm)

MR16



MOL = 3 1/4 in. (44 mm)
Dia. = 2 in. (51 mm)

Order code	Description	Watts (W)	Base	Volts (V)	Finish	Beam angle (°)	Average life (hrs)	Initial lumens (lm)	Case qty
ES16									
55563	H50GU10/FL/2.5M/120V/ELUME	50	GU10	120	Clear	35	2 500	475	12
J									
55582	H100T3/79mm/R7S/130V/ELUME 2P	100	R7S	130	Clear	N/A	2 000	1 150	12
55583	H150T3/79mm/R7S/130V/ELUME 2P	150	R7S	130	Clear	N/A	2 000	2 280	24
55584	H300T3/119mm/R7S/130V/ELUME 2P	300	R7S	130	Clear	N/A	2 000	5 100	24
55585	H500T3/119mm/R7S/130V/ELUME 2P	500	R7S	130	Clear	N/A	2 000	9 450	12
JC									
55586	H10JC/2M/G4/12V/ELUME 2P	10	G4	12	Clear	N/A	2 000	95	12
55587	H20JC/2M/G4/12V/ELUME 2P	20	G4	12	Clear	N/A	2 000	240	12
55588	H50JC/2M/GY6.35/12V/ELUME 2P	50	GY6.35	12	Clear	N/A	2 000	785	12
JD									
59227	H40JD/42MM/CL/2M/G9/130V/ELUME	40	G9	130	Clear	N/A	2 000	450	100
59228	H40JD/42MM/F/2M/G9/130V/ELUME	40	G9	130	Frost	N/A	2 000	450	100
59229	H50JD/42MM/CL/2M/G9/130V/ELUME	50	G9	130	Clear	N/A	2 000	550	100
59225	H50JD/42MM/F/2M/G9/130V/ELUME	50	G9	130	Frost	N/A	2 000	550	100
55589	H75T3/CL/2M/E11/130V/ELUME 2P	75	E11	130	Clear	N/A	2 000	1 200	12
55590	H100T3/CL/2M/E11/130V/ELUME 2P	100	E11	130	Clear	N/A	2 000	1 650	24
MR16									
55591	H20MR16/FL/2M/GU5.3/12V/ELUME 2P	20	GU5.3	12	Clear	38	2 000	245	12
55592	H35MR16/FL/2M/GU5.3/12V/ELUME 2P	35	GU5.3	12	Clear	38	2 000	430	60
55593	H50MR16/FL/2M/GU5.3/12V/ELUME 2P	50	GU5.3	12	Clear	38	2 000	645	60
55594	H50MR16/FL/CG/GU5.3/12V/ELUME 2P	50	GU5.3	12	Clear	38	2 000	630	12