

PAR, BR and R lamps offer the perfect replacement to traditional halogen PAR and incandescent reflector lamps.

Features

- PAR and BR are suitable for outdoor use (base up)
- Operating temperatures:
Non-dimmable: -23°C/-10°F to 55°C/131°F
Dimmable: -20°C/-4°F to 60°C/140°F
- Amalgam technology
-  Visit our website for a complete listing of all STANDARD ENERGY STAR qualified products



PAR-BR-R

PAR20



MOL = 3 1/4 in. (95 mm)
Dia. = 2 15/32 in. (63 mm)

PAR30LN



MOL = 4 29/32 in. (125 mm)
Dia. = 3 3/4 in. (95 mm)

PAR38



MOL = 5 15/32 in. (139 mm)
Dia. = 4 13/16 in. (122 mm)



MOL = 4 7/8 in. (124 mm)
Dia. = 4 23/32 in. (120 mm)

R20



MOL = 4 7/8 in. (124 mm)
Dia. = 2 7/16 in. (62 mm)

BR30



MOL = 5 19/32 in. (142 mm)
Dia. = 3 21/32 in. (93 mm)

BR40



MOL = 6 11/32 in. (161 mm)
Dia. = 4 13/16 in. (122 mm)

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Halogen equivalent (W)	Dimmable (Yes/No)
------------	-------------	-----------	------	------------------	-----	--------------------	---------------------	----------	------------------------	-------------------

PAR

14100	CF9/27K/PAR20/E26/STD	9	E26	2 700	82	8 000	300	48	50	N
14101	CF9/30K/PAR20/E26/STD	9	E26	3 000	82	8 000	300	48	50	N
14102	CF9/35K/PAR20/E26/STD	9	E26	3 500	82	8 000	300	48	50	N
14103	CF9/41K/PAR20/E26/STD	9	E26	4 100	82	8 000	300	48	50	N
14104	CF9/50K/PAR20/E26/STD	9	E26	5 000	82	8 000	300	48	50	N
60096	CF15/27K/PAR30LN/E26/STD	15	E26	2 700	82	8 000	700	24	75	N
14015	CF15/30K/PAR30LN/E26/STD	15	E26	3 000	82	8 000	700	24	75	N
14026	CF15/35K/PAR30LN/E26/STD	15	E26	3 500	82	8 000	700	24	75	N
61513	CF15/41K/PAR30LN/E26/STD	15	E26	4 100	82	8 000	700	24	75	N
14028	CF15/50K/PAR30LN/E26/STD	15	E26	5 000	82	8 000	700	24	75	N
59615	CCFL18/27K/PAR38/25M/E26/STD	18	E26	2 700	82	25 000	800	32	75	Y
59614	CCFL18/41K/PAR38/25M/E26/STD	18	E26	4 100	82	25 000	800	32	75	Y
60944	CF23/27K/PAR38/E26/STD	23	E26	2 700	82	8 000	1 200	24	90	N
60097	CF23/30K/PAR38/E26/STD	23	E26	3 000	82	8 000	1 200	24	90	N
60098	CF23/35K/PAR38/E26/STD	23	E26	3 500	82	8 000	1 200	24	90	N
14013	CF23/41K/PAR38/E26/STD	23	E26	4 100	82	8 000	1 200	24	90	N
14014	CF23/50K/PAR38/E26/STD	23	E26	5 000	82	8 000	1 200	24	90	N

BR

14163	CF13/27K/BR30/E26/STD	13	E26	2 700	82	8 000	700	24	60	N
61081	CF16/27K/BR30/E26/STD	16	E26	2 700	82	10 000	750	24	60	N
14164	CF23/27K/BR40/E26/STD	23	E26	2 700	82	10 000	1 300	24	120	N

R shape

14162	CF11/27K/R20/E26/STD	11	E26	2 700	82	8 000	350	48	50	N
58397	CF14/27K/R20/E26/STD	14	E26	2 700	82	8 000	500	48	60	N
58934	CF16/D/27K/R30/E26/STD	16	E26	2 700	82	8 000	700	12	65	Y