



Features

- Suitable for outdoor applications (base up) *
- Suitable for use in enclosed fixtures **
- Dimmable (where specified)
- Operating temperatures:
Non-dimmable: -23°C/-10°F to 55°C/131°F
Dimmable: -20°C/0°F to 50°C/123°F
- Amalgam technology
-  Visit our website for a complete listing of all STANDARD ENERGY STAR qualified products

A15



MOL = 4 1/8 in. (103 mm)
Dia. = 2 1/2 in. (53 mm)

A16



MOL = 4 7/16 in. (113 mm)
Dia. = 2 5/8 in. (55 mm)

A19



MOL = 4 7/8 in. (124 mm)
Dia. = 2 1/2 in. (60 mm)

T19



MOL = 5 1/2 in. (140 mm)
Dia. = 2 3/8 in. (60 mm)

T23



MOL = 6 1/8 in. (162 mm)
Dia. = 2 7/8 in. (73 mm)

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)	Dimmable (Yes/No)
------------	-------------	-----------	------	------------------	-----	--------------------	---------------------	----------	-----------------------------	-------------------

A shape

58445	CF4/27K/A15/E26/STD	4	E26	2 700	82	8 000	225	25	25	N
58446	CF9/27K/A16/E26/STD */**	9	E26	2 700	82	8 000	470	40	40	N
58394	CF14/27K/A19/E26/STD */**	14	E26	2 700	82	8 000	800	60	60	N
58936	CF16/D/27K/A19/E26/STD	16	E26	2 700	82	8 000	800	60	60	Y

Capsules*

56268	CF15/27K/T19/E26/STD	15	E26	2 700	82	8 000	800	60	60	N
58395	CF15/30K/T19/E26/STD	15	E26	3 000	82	8 000	800	60	60	N
58396	CF15/41K/T19/E26/STD	15	E26	4 100	82	8 000	800	60	60	N
56269	CF15/50K/T19/E26/STD	15	E26	5 000	82	8 000	800	60	60	N
56270	CF20/27K/T19/E26/STD	20	E26	2 700	82	8 000	1 200	75	75	N
58400	CF20/30K/T19/E26/STD	20	E26	3 000	82	8 000	1 350	75	75	N
58401	CF20/41K/T19/E26/STD	20	E26	4 100	82	8 000	1 350	75	75	N
56271	CF20/50K/T19/E26/STD	20	E26	5 000	82	8 000	1 200	75	75	N
56272	CF26/27K/T23/E26/STD	26	E26	2 700	82	8 000	1 450	100	100	N
56273	CF26/50K/T23/E26/STD	26	E26	5 000	82	8 000	1 450	100	100	N

Features

- Suitable for outdoor applications (base up) *
- Suitable for use in enclosed fixtures **
- Amalgam technology
- Operating temperatures:
-23°C/-10°F to 55°C/131°F
-  Visit our website for a complete listing of all STANDARD ENERGY STAR qualified products



DECORATIVE

Globe G25



MOL = 4 11/32 in. (110 mm)
Dia. = 2 17/32 in. (64 mm)

Globe G30



MOL = 5 3/8 in. (143 mm)
Dia. = 3 3/4 in. (95 mm)

Candle
(E12 & E26)
3 Watts



MOL = 4 11/32 in. (112 mm)
Dia. = 1 13/32 in. (36 mm)

5 Watts



MOL = 4 13/32 in. (100 mm)
Dia. = 1 13/32 in. (36 mm)

7 Watts



MOL = 4 13/16 in. (122 mm)
Dia. = 1 21/32 in. (42 mm)

9 Watts



MOL = 4 13/32 in. (112 mm)
Dia. = 1 9/16 in. (40 mm)

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
------------	-------------	-----------	------	------------------	-----	--------------------	---------------------	----------	-----------------------------

Candles

58413	CF3/27K/CANDLE/E26/STD	3	E26	2 700	82	8 000	80	15	15
59841	CF5/T2/27K/CANDLE/E12/STD	5	E12	2 700	82	8 000	220	25	25
59842	CF5/T2/27K/CANDLE/E26/STD	5	E26	2 700	82	8 000	220	25	25
14167	CF7/27K/CANDLE/E12/STD	7	E12	2 700	82	8 000	350	30	30
14168	CF7/27K/CANDLE/E26/STD	7	E26	2 700	82	8 000	350	30	30
59843	CF9/T2/27K/CANDLE/E12/STD	9	E12	2 700	82	8 000	450	40	40
59844	CF9/T2/27K/CANDLE/E26/STD	9	E26	2 700	82	8 000	450	40	40

Globes

58439	CF9/27K/G25/E26/STD */**	9	E26	2 700	82	8 000	495	40	40
58440	CF14/27K/G25/E26/STD */**	14	E26	2 700	82	8 000	850	60	40
61140	CF20/27K/G30/E26/STD	20	E26	2 700	82	8 000	1 100	60	60
57192	CF25/27K/G30/E26/STD	25	E26	2 700	82	8 000	1 300	100	60