



MOL = 6 1/8 in. (154 mm)  
Dia. = 2 1/4 in. (57 mm)



MOL = 4 13/32 in. (112 mm)  
Dia. = 1 29/32 in. (45 mm)



11 watts MOL = 4 1/4 in. (108 mm)  
Dia. = 2 3/8 in. (60 mm)  
15-20 watts MOL = 5 1/8 in. (130 mm)  
Dia. = 2 7/8 in. (58 mm)  
23 watts MOL = 5 7/8 in. (138 mm)  
Dia. = 2 7/8 in. (62 mm)

The **TRILIGHT SPIRAL LAMP** provides three intensities of light (13, 20 and 25 watts), which are equivalent to incandescent lamps of 60, 75 and 100 watts.

### Features

- Operating temperatures: -23°C/-10°F to 55°C/131°F
-  Visit our website for a complete listing of all **STANDARD ENERGY STAR** qualified products

The recommended use for **BUG LIGHT** is in outdoor patio/garden fixtures around seating and barbecue areas. Can also be used as other regular or coloured spirals.

### Features

- Contains special yellow phosphors specifically designed to repel insects.
- Operating temperatures: -23°C/-10°F to 55°C/131°F

**HIGH POWER FACTOR** lamps are more efficient because they have a low total harmonic distortion (THD).

### Features

- Suitable for use in totally enclosed fixtures
- Operating temperatures: -29°C/-20°F to 71°C/160°F
- Amalgam technology
-  Visit our website for a complete listing of all **STANDARD ENERGY STAR** qualified products

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
<b>High Power Factor</b>									
58393	CF11/HPF/27K/SPIRAL/E26/STD	11	E26	2 700	82	10 000	500	48	40
58404	CF20/HPF/27K/SPIRAL/E26/STD	20	E26	2 700	82	10 000	1 200	48	75
57862	CF23/HPF/27K/SPIRAL/E26/STD	23	E26	2 700	82	10 000	1 400	48	100
<b>Trilight</b>									
58959	CF13/20/25/27K/SPIRAL/E26/STD	13 20 25	E26	2 700	80	8 000	900 1 200 1 550	48	60 75 100
<b>Bug Light</b>									
59162	CF13/Y/BG/SPIRALE/E26/STD	13	E26	Yellow	N/A	10 000	N/A	48	60