

Features

- Dimmable (where specified)
- Operating temperatures:
Non-dimmable: -18°C/0°F to 50°C/123°F
Dimmable: -20°C/-4°F to 60°C/140°F
-  Visit our website for a complete listing of all STANDARD ENERGY STAR qualified products



T3 SPIRALS

5 Watts (E26 & E12)



MOL = 3 ¹⁵/₃₂ in. (88 mm) Dia. = 1 ⁷/₃₂ in. (39 mm)
MOL = 3 ¹/₈ in. (79 mm) Dia. = 1 ⁷/₃₂ in. (39 mm)

7 Watts



MOL = 3 ²⁷/₃₂ in. (98 mm) Dia. = 1 ²⁵/₃₂ in. (45 mm)

11 Watts



MOL = 4 ⁹/₃₂ in. (109 mm) Dia. = 1 ¹³/₁₆ in. (46 mm)

14 Watts



MOL = 4 ²¹/₃₂ in. (118 mm) Dia. = 1 ²⁵/₃₂ in. (45 mm)

23 Watts



MOL = 4 ¹⁵/₃₂ in. (139 mm) Dia. = 2 ¹/₈ in. (54 mm)

26 Watts



MOL = 5 ⁷/₁₆ in. (138 mm) Dia. = 2 ³/₁₆ in. (59 mm)

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)	Dimmable (Yes/No)
------------	-------------	-----------	------	------------------	-----	--------------------	---------------------	----------	-----------------------------	-------------------

T3 Spirals

60930	CF5/27K/SPIRAL/E26/STD	5	E26	2 700	82	10 000	270	48	25	N
58391	CF5/27K/SPIRAL/E12/STD	5	E12	2 700	82	8 000	250	48	25	N
14137	CF7/27K/SPIRAL/E26/STD	7	E26	2 700	82	10 000	400	48	30	N
14139	CF11/27K/SPIRAL/E26/STD	11	E26	2 700	82	10 000	700	48	40	N
58935	CF14/D/27K/SPIRALE/E26/STD	14	E26	2 700	82	8 000	800	48	60	Y
59611	CF23/D/27K/SPIRAL/E26/STD	23	E26	2 700	82	8 000	1 600	48	100	Y
58406	CF26/30K/SPIRAL/E26/STD	26	E26	3 000	82	10 000	1 850	48	100	N
58407	CF26/35K/SPIRAL/E26/STD	26	E26	3 500	82	10 000	1 850	48	100	N
58408	CF26/41K/SPIRAL/E26/STD	26	E26	4 100	82	10 000	1 850	48	100	N
14161	CF26/50K/SPIRAL/E26/STD	26	E26	5 000	82	10 000	1 850	48	100	N
58409	CF26/65K/SPIRAL/E26/STD	26	E26	6 500	82	10 000	1 850	48	100	N
58442	CF27/27K/SPIRAL/E26/STD	27	E26	2 700	82	10 000	1 850	48	100	N