



## WATER **VALVES**



The Robertshaw® E-1, E-2 and E-2T Mixing Water Valve Series is designed for laundry clothes washer applications. The E-1 models are non-regulated, the E-2 models have flow control in the outlet, and the E-2T models have an additional thermistor added for temperature monitoring.

#### **Features and Benefits**

- Pilot-operated diaphragm provides high flow capacity with minimum power requirements
- Compact design compared to predecessor valves to allow more flexibility for applications
- Flange mounting with screw boss is molded into the body for ease of installation
- Design uses a staked coil L frame with drawn pole sleeves to eliminate loose or missing pole pieces
- Improved coil bobbin design reduces problems
- Slow closing operators reduce water hammer and extend valve life
- Spin-weld assembly minimizes problems caused by loose or missing screws
- Suitable for applications using liquids up to 160°F (71°C)
- Quiet operation
- Stainless steel inlet screens with 60 x 60 mesh (60 holes/inch in both x and y directions)

| REPLACEMENT INFORMATION |                        |                |  |  |  |  |  |  |  |
|-------------------------|------------------------|----------------|--|--|--|--|--|--|--|
| Part Numbers            | Replaces               | Factory Number |  |  |  |  |  |  |  |
| CW-164                  | Whirlpool 3952164      | K-69046        |  |  |  |  |  |  |  |
| CW-347                  | Whirlpool 3979347      | K-75398        |  |  |  |  |  |  |  |
| CW-400                  | Electrolux 134211400   | K-75712        |  |  |  |  |  |  |  |
| CW-471                  | Whirlpool 461970229471 | K-76422        |  |  |  |  |  |  |  |
| CW-551                  | Whirlpool 461970201551 | K-74969        |  |  |  |  |  |  |  |












E-1 E-2 & E-2T SERIES


WATER VALVES


#### **PRODUCT DRAWINGS**



















E-1 E-2 & E-2T SERIES

WATER VALVES

### **PRODUCT DRAWINGS**









# E-1 WATER F-2 & E-2T VALVES SERIES

| SPECIFICATIONS |  |                         |               |              |                       |           |                  |                     |                      |            |  |  |
|----------------|--|-------------------------|---------------|--------------|-----------------------|-----------|------------------|---------------------|----------------------|------------|--|--|
| Part Numbers   | Description  | Flow Rate               | Inlet         | Outlet       | Operating<br>Pressure | Terminals | Body<br>Material | Thermistor          | Electrical<br>Rating | Power      |  |  |
| CW-164         | Residential<br>Clothes Washer Mixing<br>Water Valve E-1  | 1.0 GPM to 6.0<br>GPM   | 3/4" 11.5 NHT | 1/2" ID Hose | 20 PSI to 120 PSI     | 1/4" Male | Polypro          | NA                  | 120V AC<br>60 Hz     | 5<br>Watts |  |  |
| CW-347         | Residential<br>Clothes Washer Mixing<br>Water Valve E-2T | 1.0 GPM to 6.0<br>GPM   | 3/4" 11.5 NHT | 3/8" ID Hose | 20 PSI to 120 PSI     | 1/4" Male | Polypro          | 50K Ohms<br>at 25°C | 120V AC<br>60 Hz     | 5<br>Watts |  |  |
| CW-400         | Residential<br>Clothes Washer Mixing<br>Water Valve E-1  | 1.8 GPM to 14.6<br>GPM  | 3/4" 11.5 NHT | 1/2" ID Hose | 20 PSI to 120 PSI     | 1/4" Male | Polypro          | NA                  | 120V AC<br>50/60 Hz  | 5<br>Watts |  |  |
| CW-471         | Residential<br>Clothes Washer Mixing<br>Water Valve E-2  | 1.69 GPM to<br>2.54 GPM | 3/4" 11.5 NHT | 3/8" ID Hose | 7.5 PSI to 147 PSI    | 1/4" Male | Polypro          | NA                  | 120V AC<br>50/60 Hz  | 5<br>Watts |  |  |
| CW-551         | Residential<br>Clothes Washer Mixing<br>Water Valve E-2  | 1.69 GPM to<br>2.54 GPM | 3/4" 11.5 NHT | 3/8" ID Hose | 7.5 PSI to 147 PSI    | 1/4" Male | Polypro          | NA                  | 120V AC<br>60 Hz     | 5<br>Watts |  |  |