











Skeleton Motors

Sleeve Bearing - Shaded Pole

3000 R.P.M.

Skeleton Motors continued from previous

Part #	Amps	Volts	HP	Stack	Rot.	Shaft	Rated	Features	Comment
R611 	0.50	115	1/215	0.55	C.W.	1.7"x.1811" 	1500 RPM 0.55 Amps 1/300 HP	C-ring groove, Cord & plug	ELECTROHOME SM601, NUTONE 23303, BROAN 3008001
R634 	0.50	208 230	1/40	1.10	C.C.W.	1.0"x7/32" 	1730 RPM 0.60 Amps 1/90 HP	Cords c/w spades	WESTCAN, DIMPLEX
R3550 	0.60	115	1/115	0.55	C.W.	1.7"x7/32" 	3000 RPM 0.60 Amps 1/115 HP	KIT-Cord & plug c/w fan blade, Rear mounting	BROAN NUTONE 65100, 33-100, C65878, EM-550, SM-550, VFM-100
R3549 	0.60	115	1/115	0.55	C.W.	1.7"x7/32" 	3000 RPM 0.60 Amps 1/115 HP	KIT-Cord & plug c/w fan blade, Front mounting	Front Mounting R3550
R601 	0.70	115	1/80	0.90	C.W.	2.2"x1/4" 	3000 RPM 0.70 Amps 1/80 HP	Cord & plug	BROAN NUTONE 30080007, 162,
R3101 	0.70	115	1/80	0.98	C.C.W.	1.6"x7/32" 	3000 RPM 0.70 Amps 1/80 HP	Cord w/ three pin two speed plug	BROAN NUTONE C52367, C27987, EM551, EM554, VFM101, VFM105, R3551
R1014 	0.70	115	1/65	0.88	C.W.	1.1"x3/16" 	3000 RPM 0.70 Amps 1/65 HP	30" cord	BLANCHARD E1014, KOOL AIR, REF PLUS, CANCOIL
R3553 	0.75	115	1/70	0.80	C.W.	1.8"x7/32" 	3000 RPM 0.75 Amps 1/70 HP	Cord w/ ring terminal	BROAN NUTONE 65104, 33-104, C66582, EM-552, SM-553, VFM-104
R3103 	0.75	115	1/70	0.80	C.W.	2.4"x7/32" 	3000 RPM 0.75 Amps 1/70 HP	Cord & plug,	BROAN NUTONE C63676, C66582, C68626, 27, EM552, 553, 555, VFM103, 104, 106
R3552 	0.80	115	1/55	0.90	C.W.	1.2"x7/32" 	3000 RPM 0.80 Amps 1/55 HP	Cord & plug, Ground wire	BROAN NUTONE 65105, 33-103, C63675 EM-552, SM-552, VFM-103

Skeleton Motors Continued on next page

Rotation determined opposite shaft end
Double shaft determined at lead end

Shaft length measured from hub
face to shaft end

www.rotom.ca

Skeleton Motors 3