

DAFCO FILTRATION GROUP®

3-PLY FILTERS—SERIES 15/40



- Up to three times the capacity and service life of other panel filters
- Longer service life means lower operating costs
- Self-gasketing perimeter assures leak-proof performance
- Media is non-allergenic, unaffected by moisture, humidity, and most corrosive chemicals
- The media will not support growth of fungus or bacteria
- Replaces pleats and fiberglass disposables
- A wide range of standard and custom sizes



DESCRIPTION

The Aerostar 3-Ply Panel and Link filters incorporate three distinct filter layers permanently heat-sealed around a sturdy internal wire-frame. The first layer acts as a high-porosity impingement filter, the second a high-density interceptor and the third a durable strainer to prevent unloading or streaming. A non-migrating tackifier between the second and third laminates assures positive filter-cake build up. This filter achieves a high level of efficiency on a wide range of particle sizes. Because no external support structure is necessary, all of the media surface is exposed to the air stream.

BENEFITS

The Aerostar 3-ply filter's media is non-allergenic, unaffected by moisture and humidity and is ideal in rooftop HVAC equipment exposed to high humidity situations. They offer the additional advantage of being linkable, and the self-healing, friction-fit frames can often eliminate the need for extra mounting hardware.

APPLICATIONS

You may choose either the panel or link form of filter construction. The link form is designed for side load slide-in systems. It eliminates any possible joint leakage, and can reduce filter change-out time by up to 70%. Both panels and links offer approximately three times the life of fiberglass panel filters. When used as pre-filters, these filters will add substantially to the life of more expensive high-efficiency filters.



DAFCO FILTRATION GROUP®

ADVANTAGES OF AEROSTAR 3-PLY

These 3-ply, triple-density filters are a substantial “step up” from conventional fiberglass filters. They offer up to triple the efficiency and triple the service life, but do not cost three times more. The heat-sealed laminated construction eliminates fiber break-off and makes the filters easier to handle with bare hands. The self-gasketing frame reduces hardware and holding devices by giving a positive friction-fit. The AeroStar 3-Ply is an ideal filter for medium-efficiency applications.

AIR FLOW CAPACITIES

Nominal Size	Capacity cfm @ 300 fpm
12 x 24	600
15 x 20	625
16 x 20	670
16 x 25	833
18 x 24	900
20 x 20	833
20 x 24	1000
20 x 25	1042
24 x 24	1200
25 x 25	1302

Initial Resistance in w.g. = .24 for All Sizes

SPECIFICATIONS

Filter Media:	3 layers of 100% synthetic fibers
Internal Frame:	9 gauge wire
Flammability:	UL900 Class 2
Recommended Final Resistance:	1.0" w.g.
Maximum Temperature:	120° F
Actual Dimension of Internal Frame:	5/8" under nominal size*

* The internal wire frame used in standard panels are manufactured to the nominal size of the filter, less 5/8". For example, the actual dimension of the wire frame for a 20"x20" 3-ply panel (part # 10872) is 19 3/8"x19 3/8"; a 5/8" smaller than both nominal dimensions.

3-PLY 15/40 PANELS

PART NUMBER	NOMINAL SIZE	CASE QTY.
10856	10 x 20	24
10857	12 x 20	24
10858	12 x 24	24
10860	14 x 20	24
10861	14 x 25	24
10862	15 x 20	24
10865	16 x 20	24
10867	16 x 24	24
10869	16 x 25	24
10870	18 x 24	24
10871	18 x 25	24
16836	20 x 20	24
10874	20 x 24	24
10875	20 x 25	24
10795	20 x 46	8
10796	20 x 48	8
10877	24 x 24	24
10879	25 x 25	24

© DFG 01/08



DAFCO FILTRATION GROUP®

Phone: 1-888-628-3458
 www.dafcofiltrationgroup.com
 e-mail: info@dafcofiltrationgroup.com

