


Erie™ Spring Return Two-Position Actuator

The PopTop™ series valve bodies and actuators provide easy installation for a variety of heating and cooling applications.


The valve's actuator can be installed after the valve body has been installed onto the fan coil, baseboard or air handler.

Features:

- Synchronous motor drive with spring return.
- Variety of voltages available.
- Mounts directly onto the body without the need for linkages or calibration.
- Manual override lever on normally closed actuators.



AHxx Series
High Close-off



AGxx Series
General Close-off

Model Chart

General Close-Off, 2-Position, Power (Open or Close): 9 to 11 Seconds; Spring Return (Open or Close): 4 to 5 Seconds

Model No.	Volts AC	Electrical Position	Temperature Range F (C)	End Of Travel Switch	Wiring
AG13A01A	24	Normally Closed	32 to 200°F (Fluid) @ 104°F (Ambient) (0 to 93°C @ 40°C)	Yes	Terminal Block
AG13A020	24			No	18 in. Leads
AG13A02A	24			Yes	
AG13B020	120			No	
AG13B02A	120			Yes	
AG13D020	208			No	
AG13D02A	208			Yes	
AG13T020	277			No	
AG13T02A	277			Yes	
AG13U020	230			No	
AG13U02A	230			Yes	
AG14A020	24		32 to 250°F (Fluid) @ 169°F (Ambient) (0 to 121°C @ 76°C)	No	
AG14A02A	24			Yes	
AG14B020	120			No	
AG14B02A	120			Yes	
AG14D020	208			No	
AG14D02A	208			Yes	
AG14T020	277			No	
AG14U020	230			No	
AG14U02A	230			Yes	
AG23A01A	24	Normally Open (can only be used on 2-way valve)	32 to 200°F (Fluid) @ 104°F (Ambient) (0 to 93°C @ 40°C)	Yes	Terminal Block
AG23A020	24			No	18 in. Leads
AG23A02A	24			Yes	
AG23B020	120			No	
AG23B02A	120			Yes	
AG23D020	208			No	
AG23D02A	208			Yes	
AG23T020	277			No	
AG23T02A	277			Yes	