



# Foundation

## Floor Sealer

Achieves uncommon levels of durability and permanency for total sealer protection.  
Gives good levelling, appearance and gloss with minimum effort.

### Reduced Environmental Impact

ECOLOGO Certified UL 2777 - Hard Floor Care Products.

### Chemical Resistant

Resists spills and stains, detergent and ice melt. Unaffected by washing and damp mopping.

### Colourless Film

Will not yellow with age.

### Dries Quickly

Faster re-coat, less "down time".

### Safe to Use

It is solvent free and non-flammable. It contains no APE or zinc.

### Available Sizes

**Code:** 53777 (4 L)  
53779 (20 L)



### Directions

Apply using a clean mop or sprayer, allowing 30-60 minutes between applications. Two or three coats are recommended. Before sealing non-resilient floors, it is recommended that a small test patch be applied and checked for adhesion after 24 hours. New non-resilient floors must be completely cured and dried before application. Surface etching is not required. Floors must be stripped, cleaned and allowed to dry thoroughly.

**Coverage:** Coverage per 4 L is 150 m<sup>2</sup> (1600 ft<sup>2</sup>) to 240 m<sup>2</sup> (2500 ft<sup>2</sup>) depending upon porosity of the floor.

### Where to use

Designed to give total sealer protection to resilient (except unsealed wood) and non-resilient (except magnesite) floors.

### Specifications

**Type:** Zinc free acrylic copolymer

**Appearance:** White liquid

**Fragrance:** Acrylic

**Viscosity:** As water

**Coating Gloss (5 coats):** 91%

**pH:** 8.7

**Non-volatile %:** 15.0

**Refractive Index:** 18.0%

**Slip Resistance:**

0.5 min (ASTM D-2047)

**Freeze-Thaw Stability:**

Passes 3 cycles

**Dry Time:** 30-60 minutes

**WHMIS:** No

**TDG:** No



**Dustbane Products Ltd.**

25 Pickering Pl., Ottawa (Ontario) K1G 5P4

[www.dustbane.ca](http://www.dustbane.ca)

613.745.6861 1.800.387.8226