

CAST IRON SUMP PUMPS



APPLICATIONS

Ideal for average to high-volume water and effluent removal in residential spaces such as basements, laundry facilities, and crawl spaces.

FEATURES & BENEFITS

- Automatic submersible sump pumps
- 1-1/2" FNPT discharge
- Piggyback float switch
- Clog-resistant design (1/2" solids handling)
- PSC motor
- 10' cord



Model	Item Number	UPC	HP	Switch	Volts	Amps	Cord Length	Gallons Per Hour at Height					Shut-Off	On/Off Levels	Min Basin Diameter
								0'	5'	10'	15'	20'			
RL-SC33T	14942744	0 10121 14167 4	1/3	Tethered	115	4.4	10'	3350	3000	2460	1860	960	25'	On: 13" Off: 5"	16" or more
RL-SC33V	14942745	0 10121 14168 1	1/3	Vertical	115	4.4	10'	3350	3000	2460	1860	960	25'	On: 7.25" Off: 2.75"	11" or more
RL-SC50T	14942746	0 10121 14169 8	1/2	Tethered	115	5.3	10'	4300	3840	3000	2220	1440	28'	On: 13" Off: 5"	16" or more
RL-SC50V	14942747	0 10121 14170 4	1/2	Vertical	115	5.3	10'	4300	3840	3000	2220	1440	28'	On: 7.25" Off: 2.75"	11" or more

Carton Specifications

Model	Length (in)	Width (in)	Height (in)	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
RL-SC33T	7"	8.75"	12.76"	29"	0.45	81	27	3
RL-SC33V	7"	8.75"	12.85"	30"	0.46	81	27	3
RL-SC50T	7"	8.75"	12.76"	32"	0.45	75	25	3
RL-SC50V	7"	8.75"	12.85"	32"	0.46	75	25	3

Cast Iron Sump Pumps

