

## **Panasonic**

## WhisperRecessed LED VENTILATION FRAN

FV-08VRE1



- ENERGY STAR rated architectural grade recessed fan/LED light
- Quiet, energy efficient and powerful 80 CFM ventilation hidden above the ceiling
- Includes (1) replaceable 14W, ENERGY STAR rated, GU24 base LED lamp
- Beautiful lighting with 6-1/2" aperture and advanced luminaire design
- LED lamp is dimmable
- Adjustable lamp positioning and deeper regression reduces glare



- Integrated 4" or 6" duct adapter
- UL listed for tub/shower enclosure when used with a GFCI protected circuit
- IC rated
- 5-year warranty on LED, 3-years on parts

\*Can be used to comply with CalGreen when controlled by the Panasonic Condensation Sensor.






ADDITIONAL BENEFITS




## The Design Solution for Bathroom Fan/LED Light Combinations

## WhisperRecessed LED -









New Lighted Model!
INCLUDED: One 14-Watt
GU24 base LED lamp/
3000 Kelvin/>80 CRI/
575 Lumens/50 LPW/
ENERGY STAR® qualified/
25,000 hours rated average life.

WhisperRecessed LED		FV-08VRE1	
Characteristics (HVI tested data for 0.1" S.P.)	Static Pressure in inches w.g.	0.1	0.25
	Air Volume (CFM)	80	66
	Noise (sones)	0.8	0.7
	Power Consumption (watts)	20.5	19.5
	Energy Efficiency (CFM/Watt)	4.0	3.4
	Speed (RPM)	1378	1501
	Current (amps)	0.17	0.17
	MAX. Current(amps)	0.19	
	Power Rating (V/Hz)	120/60	
Specifications	Motor Type	AC	
	Type of Motor Bearing	Ball	
	Thermal Fuse Protection	Yes	
	Blower Wheel Type	Sirocco	
	ENERGY STAR Qualified	Yes	
Installation	Duct Diameter (Inches)	4" or 6"	
	Housing Collar Opening (Inches)	6-1/2" Round	
	Trim Outer Diameter (Inches)	7-1/4" Round	
Light Specifications	Lamp Watts	1 x 14	
	Lumens (lm)	575lm	
	Lumens Per Watt (LPW)	50LPW*	
	Color Rendering Index	>80	
	Color Temperature (Kelvin)	3000K	
	Rated Life (hours)	25,000	
	Lamp Model #	LPHT14D	
	Type of Lamp Socket	GU24	
Shipping	Gross Weight (lbs)	10.8	
Approved Code/Standard/ Regulation	UL tub/Shower Enclosure	Yes	
	CalGreen	Yes**	
	Washington VIAQ Code	Yes	
	California Title 24 Compliant	Yes	
	Mfg in ISO 9001 Certified Facility	Yes	

<sup>\*</sup>As tested by an EPA recognized lab \*\*Can be used to comply with CalGreen when controlled by the Panasonic Condensation Sensor.

NOTE: 0.25" w.g. = Installed Performance







Panasonic Eco Solutions of North America Eco Products Division

Two Riverfront Plaza Newark, NJ 07102 us.panasonic.com/ventfans

ventfans@us.panasonic.com

**For Order Information** 

PHONE: 866-292-7299 FAX: 888-553-0723