Material Safety Data Sheet



Revision Number: 001.0 Issue date: 10/20/2014

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: LePage PL Concrete, Crack, and

Masonry Sealant

Product use: Sealant

Region: Canada

Company address:Contact information:Henkel Canada CorporationTelephone: 800.624.7767

2515 Meadowpine Boulevard MEDICAL EMERGENCY Phone: Poison Control Center Mississauga, Ontario L5N 6C3 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

1619518

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: high viscosity WHMIS hazard class: D.2.B, D.2.A, B.3

Color: grey Odor: Slight

WARNING: COMBUSTIBLE!

HARMFUL IF INHALED.

CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY CAUSE ALLERGIC SKIN AND RESPIRATORY REACTION.

Relevant routes of exposure: Inhalation, Skin, Eyes, Ingestion

Potential Health Effects

Inhalation: As a result of previous repeated overexposures or a single large dose, certain individuals will

develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been reported to cause lung damage. Dryness of nasal passages, sore throat, cough, tightness of chest, shortness of breath. Persons suffering from allergic reactions to isocyanates should avoid contact with the product. This product may cause sensitization by inhalation and skin

contact. May cause respiratory tract irritation.

Skin contact: Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals.

This product may discolor the skin. Contact with eyes will cause irritation.

Ingestion: Ingestion of this product may cause nausea, vomiting and diarrhea.

Existing conditions aggravated by

Eye contact:

exposure:

IDH number: 1619518

Development of preexisting skin or lung allergy symptoms may increase. Asthma.

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Limestone	1317-65-3	30 - 60
Bis(2-propylheptyl) phthalate	53306-54-0	5 - 10
Stoddard solvent, <0.1% Benzene	8052-41-3	5 - 10
Talc	14807-96-6	5 - 10
Calcium oxide	1305-78-8	1 - 5
Toluene-2,4-diisocyanate	584-84-9	1 - 5
Titanium dioxide	13463-67-7	5 - 10
Toluene-2,6-diisocyanate	91-08-7	1 - 5

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. Immediate

medical treatment necessary.

Skin contact: Wash affected area immediately with soap and water. If symptoms develop

and persist, get medical attention. Remove contaminated clothes.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Do not induce vomiting, seek medical advice immediately.

Notes to physician: An individual having a dermal or pulmonary sensitization reaction to this

material should be removed from further exposure to any

diisocyanate. Treatment based on judgement of the physician in response to

reactions of the patient.

5. FIRE FIGHTING MEASURES

Flash point: 89 °C (192.2 °F) Certificate of Supplier

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available.

Flammable/Explosive limits - upper:

Not available.

Extinguishing media: Water fog. Foam Carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: None known

Hazardous combustion products: Nitrous gases Irritating fumes. Isocyanate vapors.

Sensitivity to Mechanical Impact: Not available.

Sensitivity to static discharge: Not available.

IDH number: 1619518

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Ensure adequate ventilation. Scrape up spilled material and place in a closed

container for disposal. Wear suitable protective clothing, gloves and eye/face

protection.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid extreme temperatures. Wash

thoroughly after handling. Protect from moisture. Use only with adequate

ventilation.

Storage: For safe storage, store between 18.3 °C (64.9 °F) and 40 °C (104°F)

Avoid moisture. Keep in a cool, well ventilated area away from heat, sparks

and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Bis(2-propylheptyl) phthalate	None	None	None	None
Stoddard solvent, <0.1% Benzene	100 ppm TWA	500 ppm (2,900 mg/m3) PEL	None	None
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
Toluene-2,4-diisocyanate	0.005 ppm TWA 0.02 ppm STEL (Sensitizer.)	0.02 ppm (0.14 mg/m3) Ceiling	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust.	None	None
Toluene-2,6-diisocyanate	0.005 ppm TWA 0.02 ppm STEL (Sensitizer.)	None	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

limits.

Respiratory protection: Observe OSHA regulations for respirator use (29 CFR 1910.134). Use a

NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Respirator with combination filter for vapor/particulate.

Eye/face protection: Safety glasses with side-shields. Full face protection should be used if the

potential for splashing or spraying of product exists.

Skin protection:Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: high viscosity Color: high viscosity grey

IDH number: 1619518 Product name: LePage PL Concrete, Crack, and Masonry Sealant Page 3 of 6

Odor: Slight

Odor threshold:Not available.pH:not applicableVapor pressure:Not available.Boiling point/range:Not available.Melting point/ range:Not applicable

Specific gravity: 1.20

Vapor density: Not available.

Flash point: 89 °C (192.2 °F) Certificate of Supplier

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available.

Insoluble

Not available.

VOC content:

2.89 %; 33 g/l

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Contact with moisture, other materials that react with isocyanates, or

temperatures above 350° F (177° C), may cause polymerization.

Hazardous decomposition products: Irritating and/or toxic fumes and gases may be emitted upon the product's

decomposition. nitrogen oxides Aromatic isocyanates. carbon oxides. carbon

monoxide Hydrogen cyanide.

Incompatible materials: Oxidizing agents. Alcohols. Water. Strong bases.

Conditions to avoid: Avoid moisture. Keep away from open flames, hot surfaces and sources of

ignition. Prolonged exposure to heat.

11. TOXICOLOGICAL INFORMATION

Toxicologically synergistic products: Not available.

IDH number: 1619518

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Limestone	No	No	No	No
Bis(2-propylheptyl) phthalate	No	No	No	No
Stoddard solvent, <0.1% Benzene	No	No	No	No
Talc	No	Group 2B	No	Group A4
Calcium oxide	No	No	No	No
Toluene-2,4-diisocyanate	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No	Group A4
Titanium dioxide	No	Group 2B	No	Group A4
Toluene-2,6-diisocyanate	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No	Group A4

Hazardous components	LD50s and LC50s	Health Effects/Target Organs
Limestone	None	Nuisance dust
Bis(2-propylheptyl) phthalate	None	No Target Organs
Stoddard solvent, <0.1% Benzene	None	Central nervous system, Irritant
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Calcium oxide	None	Irritant, Corrosive, Eyes
Toluene-2,4-diisocyanate	Oral LD50 (RAT) = 5,800 mg/kg Inhalation LC50 (RAT, 4 h) = 14 mg/l Inhalation LC50 (RABBIT) = 11 mg/l	Allergen, Eyes, Irritant, Lung, Respiratory, Some evidence of carcinogenicity
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Toluene-2,6-diisocyanate	None	Allergen, Bone Marrow, Corrosive, Eyes, Irritant, Mutagen, Respiratory, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Reviewed MSDS. Reissued with new date.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

IDH number: 1619518

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.