

Single Shaft-115 Volts - Open & Totally Enclosed

Sleeve Bearing - Shaded Pole & P.S.C.



Fig.1
R2197



Fig.2
R2195
R2194



Fig.3
R2198
R2654




Fig.4
R2269

Motors



Fig.5
R6920



Fig.6
R2343



Fig.7
R2653



Fig.8
R2698



Fig.9
R2930
R2932
R2940
R2942
R2360




Fig.10
R2980

Part #	HP	Amps	Spd/RPM	Rot.	Shaft	Body	Encl.	Type	Comment	Fig.
R2360	1/15	1.70	1/1050	C.C.W.	2.8"x1/2"	3.59	T.E	S.P.	REZNOR 45330, 45331, 54332, FASCO D143, U.E. 360	9
R2269	1/15	2.40	1/1050	C.C.W.	3.0"x1/2"	3.00	OPEN	S.P.	KEEPRITE 160269, FASCO 7151-2850, 7151-3862	4
R6920	1/15	2.40	1/1050	C.C.W.	3.0"x3/8"	3.80	T.E.	S.P.	KEEPRITE, INTERCITY, LENNOx P8-6920	5
R2197	1/14	1.20	3/820	C.C.W.	3.4"x1/2"	3.80	OPEN	7.5/370	TEMSPEC DE3E142N	1
R2194	1/14	1.25	3/820	C.C.W.	3.4"x1/2"	3.22	OPEN	7.5/370 INC.	TEMSPEC DE3E141N	2
R2198	1/14	1.25	3/820	C.C.W.	4.1"x1/2"	3.22	OPEN	7.5/370	TEMSPEC DE3E142N	3
R2195	1/12	2.10	3/740	C.C.W.	4.0"x1/2"	3.60	OPEN	7.5/370 INC.	TEMSPEC DE3F056N	2
R2653	1/12	2.90	3/1050	C.W.	1.6"x1/2"	3.40	OPEN	S.P.	GENERAL REPLACEMENT	7
R2654	1/12	3.10	3/1050	C.C.W.	2.5"x1/2"	2.65	OPEN	S.P.	G.E. 5KSP29Dx1906, FASCO D1054	4
R2930	1/10	4.00	1/1050	C.W.	2.3"x3/8"	4.80	OPEN	S.P.	G.E. 2121, 2122, 2223, 2321,,2322 Dual Voltage	9
R2932	1/10	4.00	1/1550	C.C.W.	2.3"x3/8"	4.80	OPEN	S.P.	G.E. 2131, 2132, 2231,2232, 2331, 2332, Dual Voltage	9
R2940	1/10	4.00	1/1050	C.W.	2.3"x3/8"	4.80	OPEN	S.P.	G.E. 2113, 2213, 2311,,2312, Dual Voltage	9
R2942	1/10	4.00	1/1550	C.W.	2.8"x3/8"	4.56	OPEN	S.P.	G.E. 2141, 2142, 2241,2242, 2341, 2342, Dual Voltage	9
R2980	1/10	3.20	3/1050	C.C.W.	3.3"x3/8"	3.80	S.E.	S.P.	GENERAL REPLACEMENT	10
R2698	1/10	3.50	1/1050	C.C.W.	2.1"x1/2"	3.00	OPEN	S.P.	BROAN A0520B2298, 30080126, 30080135	8

Motors continued next page

Rotation determined opposite shaft end
Double shaft determined at lead end

Shaft length measured from hub
face to shaft end

www.rotom.ca