

LED tube replacement lamps offer the perfect alternative for fluorescent lamps while minimizing mercury output, increasing efficiency, ideal for any application.

- Compatible with traditional electronic IS ballasts
- Glass encasing ensures protection against tube yellowing and brittleness
- Integrated driver for easy installation while allowing the fixture to keep its certification – no additional wiring needed
- Eliminates costly re-lamping charges
- Eliminates the start-up time of traditional fluorescent lamps



Order code	Description	Average System Wattage (W)			Volts (VAC)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)			Dimmable (Y/N)	Length in. (mm)	Case qty
		LBF	NBF	HBF						LBF	NBF	HBF			

## T8

Dia. : 1 in. (26 mm)

63244	LED/T8/12W/840/IS/24/STD	10	12	17	120-277/347	G13	4 000	85	50 000	1 000	1 200	1 700	N	24 (610)	12
63245	LED/T8/17W/840/IS/36/STD	14	17	20	120-277/347	G13	4 000	85	50 000	1 400	1 700	2 000	N	36 (915)	12
63247	LED/T8/18W/840/IS/48/STD	15	18	26	120-277/347	G13	4 000	85	50 000	1 500	1 800	2 600	N	48 (1 220)	12
63248	LED/T8/18W/850/IS/48/STD	15	18	26	120-277/347	G13	5 000	85	50 000	1 500	1 800	2 600	N	48 (1 220)	12
63249	LED/T8/22W/835/IS/48/STD	18	22	30	120-277/347	G13	3 500	85	50 000	1 800	2 200	3 000	N	48 (1 220)	12
63161	LED/T8/22W/840/IS/48/STD	18	22	30	120-277/347	G13	4 000	85	50 000	1 800	2 200	3 000	N	48 (1 220)	12
63250	LED/T8/22W/850/IS/48/STD	18	22	30	120-277/347	G13	5 000	85	50 000	1 800	2 200	3 000	N	48 (1 220)	12



For a complete list of compatible dimmers and DLC qualified products, please visit [www.standardpro.com](http://www.standardpro.com)

# T8



- ▶ PTFE coated lamps help contain glass if a lamp is broken
- ▶ Shatterproof to protect employees, production, customers, and your business reputation
- ▶ Food safe, accepted by the Canadian Food Inspection Agency (CFIA)
- ▶ Perfect for kitchens, art galleries, museums and schools



Safety MaxT8



Order code	Description	Average System Wattage (W)			Volts (VAC)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)			Dimmable (Y/N)	Length		Case qty
		LBF	NBF	HBF						LBF	NBF	HBF		in.	(mm)	

## SAFETY MAX T8

Dia. : 1 in. (26 mm)

63163	LED/T8/22W/840/IS/48/STD/SMX	18	22	30	120-277/347	G13	4 000	85	50 000	1 800	2 156	3 000	N	48	(1 220)	12
-------	------------------------------	----	----	----	-------------	-----	-------	----	--------	-------	-------	-------	---	----	---------	----



For a complete list of compatible dimmers and DLC qualified products, please visit [www.standardpro.com](http://www.standardpro.com)

# Safety Max T8