

Class 125, Bronze Disc, Solder Swing Check



	Г
Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	





DESCRIPTION

The Apollo Model 161S (61Y Series) Swing Check provides a cost effective "Made in the USA" alternative to globally sourced check valves. These valves are cast, machined, assembled, and tested in South Carolina. The Apollo Swing Check can be installed in either horizontal or vertical line with upward flow.

FEATURES

- · Renewable Bronze Seat Disc
- Dezincification Resistant
- 100% Factory tested per MSS
- Solder Connection
- 100% Cast, Machined and Assembled in the US
- ARRA Compliant

PERFORMANCE RATING

- Saturated Steam: 125 psi (8.6 Bar) to 353°F(178°C)
- Cold Working Pressure: 200 psi (13.8 Bar) at 100°F
- Temperature Range*: -20°F to 406°F
- * Valves should be in open position to allow complete drainage during freezing conditions.

STANDARD MATERIALS LIST

Part Name	Material
Body	ASTM B62 Bronze
Сар	ASTM B62 Bronze
Hanger	304 Stainless Steel
Pin	304 Stainless Steel
Seat	ASTM B62 Bronze
Plug	ASTM B16 Brass

STANDARDS

- MSS SP-80, "Bronze Gate, Globe & Check Valves",
- ASME B16.18, "Cast Copper Alloy Solder Joint Pressure Fittings
- MSS SP-104, "Wrought copper solder joint pressure fittings"
- Canadian Registration Number 0C14667.5

ORDER INFORMATION

DIMENSIONS

Model Number	Part Number	Size (in.)	Height (in.)	Length (in.)	Weight (lbs)	Cv (gpm)
161S12	61Y-093-01	1/2"	1.65	2.53	.62	7.0
161534	61Y-094-01	3/4"	1.9	3.36	.91	12.0
161S1	61Y-095-01	1"	2.26	4.07	1.7	28.6
1615114	61Y-096-01	1-1/4"	2.99	5.28	3.2	39.0
161S112	61Y-097-01	1-1/2"	2.99	5.28	2.7	56.0
161S2	61Y-098-01	2"	3.74	6.50	4.9	152.0
161S212	61Y-099-01	2-1/2"	5.11	8.30	9.7	198.0
16153	61Y-090-01	3"	6.05	9.58	15.0	242.0

Warning: Do not use in reciprocating compressor service.

Apollo Valves, Manufactured by **Conbraco Industries, Inc.** 701 Matthews Mint-Hill Road, Matthews, NC 28105 USA www.**apollovalves**.com | (704) 841-6000

