

MATERIAL SAFETY DATA SHEET (MSDS)

Fryer & Griddle

Fryer and Griddle Cleaner

Specialty Cleaners

SECTION I	► PRODUCT IDENTIFICATION			
Product Name		Product Type		WHMIS Classification
Fryer & Griddle		Fryer and Griddle Cleaner		D2B, E

SECTION II HAZARDOUS INGREDIENTS			
Chemical Name	Cas Registry No.	%	Toxicity
Potassium Hydroxide	1310-58-3	10-30	LD50ORAL (RAT) 365 mg/kg

SECTION III ► PHYS	SICAL DATA				
Appearance	Odour	рН	Boiling Point	Specific Gravity	Solubility in Water
Clear, colourless liquid	Unscented	14	100 °C	1.124	100 %

SECTION IV FIRE AND EXPLOSION HAZARD DATA Flash Point (°C): None Extinguishing media: Not Applicable Special fire fighting procedures: None Unusual fire and explosion hazards: None

SECTION V ► TOXICOLOGICAL PROPERTIES	
HAZARD RATING: Health = 3 Flammability = 0 Reactivity = 1	Dating Custom
Swallowing: Irritating to gastrointestinal tract	Rating System 0 = Insignificant
Inhalation: May cause severe irritation to respiratory tract	1 = Slight
Skin Absortion: Unknown	2 = Moderate
Skin Contact: May cause severe burns	3 = High
Eye Contact: May cause severe burns and permanent damage	4 = Extreme
Special Warning: None	

SECTION VI ► FIRST AID MEASURES			
Ingestion: Drink 3-4 glasses of milk or water. Call a physician.			
Inhalation: Remove to fresh air. Call a physician.			
Skin: Flush with water for 20 minutes. If irritation persists, call a physician.			

SECTION VII ► REACTIVITY DATA

Stable: Yes

Conditions to avoid: None

Incompatibility with other materials: Strong acids, oxidizers, aluminum, tin, zinc, organic materials

Hazardous decomposition products: None Hazardous polymerization: Will not occur.

SECTION VIII ► PREVENTIVE MEASURES

Hand protection: Yes (Wear chemical resistant gloves)

Eye protection: Yes (Wear goggles or safety glasses with side shields)

Eyes: Flush with water for at least 20 minutes. Call a physician immediately.

Ventilation: General

Respiratory protection: None

Other protective equipment: In case of spills, wear chemical resistant apron and boots.

Steps to be taken in case material is released or spilled: Mop up spillage. Rinse spill area with water and allow to dry.

Waste disposal method: Flush with water into waste systems in accordance with municipal, provincial and federal regulations.

Precautions to be taken in handling and storage: Normal handling processes. Inside storage at 4-40 °C recommended.

Other precautions: Follow label use instructions.

UN: 1760 TDG Class: 8 Packing Group: II

TDG Emergency Telephone Number: 613-996-6666 (COLLECT)

SECTION IX ► PREPERATION DATA

Prepared by: M. Mikoluk

Last updated: June 1, 2015

Location: Dustbane Products Limited, 25 Pickering Place, Ottawa, Ontario, K1G 5P4 – 613-745-6861

Fryer and Griddle

Fryer and Griddle Cleaner

"Quickly penetrates and emulsifies baked on grease, oil and carbon on metal surfaces, leaving behind a clean and odour-free surface."

FEATURES AND BENEFITS

Contains a rust inhibitor: Excellent for griddles and other metal surfaces.

Free rinsing: Easily rinsed with only water.

Concentrated caustic formula: Quickly penetrates and emulsifies baked on grease, oil and carbon on metal surfaces.

Effective surfactants: Helps suspend loosened soils, oils, fats and carbon which are then easily rinsed off.

Hard water stable: May be used in all degrees of water hardness.

WHERE TO LISE

To be used for the quick removal of baked on carbon and fat from griddles, deep fryers, ovens, barbecues and grills.

HOW TO USE

Deep Fryers: Scrape off or hose down to remove excess grease. Fill up to 10 cm (4") from the top using cold water. Dilute 1:27-1:40 and boil the solution for 30 minutes. Drain and flush off using hot water. Scrub the grease residue while it is still warm. Rinse well with potable water, then wipe dry.

Griddles: Prepare a 1:1 solution and apply liberally using a cloth or brush. Let the solution work for 5-10 minutes; wipe clean using a damp cloth. Rinse well with potable water and wipe dry.

Oven: Preheat oven to 80°C (180°F) then shut-off before applying. Using a brush, apply the concentrate directly to walls, racks, burners and glass. Let work for 5-15 minutes. Stubborn areas may need light rubbing using a soft nylon scrubbing pad. Rinse well with potable water, then wipe dry. DO NOT USE ON ALUMINUM SURFACES.

SPECIFICATIONS

Appearance: Clear, colourless liquid

Fragrance: None
Viscosity: As water
Actives %: 16.5
pH (conc.): >14.0
pH (1%): 12.5

Solvent: None
Phosphate: None
WHMIS: Yes

TDG: Yes