

Features

- 4 pole 20, 25, 30 & 40 amp
- Features lug, spade terminals and protective covers
- Totally enclosed
- Compact size
- Universal galvanized mounting plates
- ARI 780/790 standards
- Push to test button
- Brass/copper terminals
- Quick connect and screw terminals on coil.
- Snap on auxiliary contacts available
- cURus approved



4 Pole Models

Part #	Poles	Full Load Amps.	Coil Voltage 50/60	Locked Rotor Amps			Resistive Amps.	Termination	Furnas #
				240V	480V	600V			
DP-4P20A24	4	20	24	120	100	80	30	Box Lug	-
DP-4P20A120	4	20	120	120	100	80	30		-
DP-4P20A240	4	20	208/240	120	100	80	30		-
DP-4P25A24	4	25	24	150	125	100	35	Box Lug	-
DP-4P25A120	4	25	120	150	125	100	35		-
DP-4P25A240	4	25	208/240	150	125	100	35		-
DP-4P30A24	4	30	24	180	150	120	40	Screw Type	42BF25AJ
DP-4P30A120	4	30	120	180	150	120	40		42BF25AF
DP-4P30A240	4	30	208/240	180	150	120	40		42BF25AG
DP-4P40A24	4	40	24	240	200	160	50	Box Lug	42CF25AJ
DP-4P40A120	4	40	120	240	200	160	50		42CF25AF
DP-4P40A240	4	40	208/240	240	200	160	50		42CF25AG