

### MATERIAL SAFETY DATA SHEET (MSDS)

## **Accolade** *Sealer and Finish*





SECTION I	► PRODUCT IDENTIFICATION				
<b>Product Name</b>		Product Type	WHMIS Classification		
Accolade		Sealer and Finish	Not Applicable		

SECTION II    HAZARDOUS INGREDIENTS			
Chemical Name	Cas Registry No.	%	Toxicity
Not Applicable			

SECTION III PHYS	► PHYSICAL DATA							
Appearance	Odour	pН	Boiling Point	Specific Gravity	Solubility in Water			
White liquid	Acrylic	8.7	100 °C	1.0	100 %			

# SECTION IV FIRE AND EXPLOSION HAZARD DATA Flash Point (°C): None Extinguising media: Not Applicable Special fire fighting procedures: None Unusual fire and explosion hazards: None

SECTION V ► TOXICOLOGICAL PROPERTIES	
<b>HAZARD RATING:</b> Health = 1 Flammability = 0 Reactivity = 0	Dating Custom
Swallowing: Slightly Toxic	Rating System  0 = Insignificant  1 = Slight  2 = Moderate  3 = High
Inhalation: Not Applicable	
Skin Absortion: Not Applicable	
Skin Contact: Slight Irritant	
Eye Contact: Slight Irritant	4 = Extreme
Special Warning: None	

SECTION VI ► FIRST AID MEASURES	
Ingestion: Drink 3-4 glasses of milk or water.	
Inhalation: Not Applicable	
Skin: Flush with water.	
Eyes: Flush with water. If irritation persists, call a physician.	

#### SECTION VII ► REACTIVITY DATA

Stable: Yes

Conditions to avoid: None

Incompatibility with other materials: None
Hazardous decomposition products: None
Hazardous polymerization: Will not occur.

#### SECTION VIII ► PREVENTIVE MEASURES

Hand protection: No
Eye protection: No
Ventilation: General
Respiratory protection: None

Other protective equipment: None

Steps to be taken in case material is released or spilled: Mop up spillage. Rinse spill area with water and allow to dry.

**Waste disposal method:** Flush with water into waste systems in accordance with municipal, provincial and federal regulations.

**Precautions to be taken in handling and storage:** Normal handling processes. Inside storage at 4-40 °C recommended.

Other precautions: Follow label use instructions.

UN: Not Applicable TDG Class: None Packing Group: Not Applicable

**TDG Emergency Telephone Number:** 613-996-6666 (COLLECT)

#### SECTION IX ► PREPERATION DATA

Prepared by: M. MikolukLast updated: June 1, 2015Location: Dustbane Products Limited, 25 Pickering Pl., Ottawa, OntarioK1G 5P4 – 613-745-6861



"Seals and finishes in one easy step: providing exceptional gloss and leveling. Specifically formulated to protect both resilient and non-resilient floors"

#### **FEATURES AND BENEFITS**

**Environmentally Friendly:** A.P.E. free

**Excellent floor finish properties:** Does not require a floor finish application, if desired, therefore saves costs and labour.

Chemical resistant: Resists spills and stains.

**Detergent resistant:** Unaffected by washing and damp mopping.

Colourless film: Will not yellow with age.

Dries quickly: Faster re-coat, saves time and labour.

**Easy to apply:** Gives good levelling, appearance and gloss with minimum effort.

Safe to use: No solvents, non-flammable.

#### WHERE TO USE

May be applied to all resilient and non-resilient floors such as vinyl, vinyl composite, rubber, linoleum, terrazo, quarry tile, slate, unglazed ceramic, brick, mexican tile and concrete.

#### **HOW TO USE**

**Preparation:** Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry.

**Application:** Using a clean mop or sprayer, apply 2-3 coats (depending on the porosity of the floor) allowing the floor to completely dry between coats, at least 30-60 minutes or more depending on humidity condition.

Coverage: Coverage per 5 L is 170 m2 (1830 ft2) to 280 m2 (3014 ft2) depending upon porosity of the floor.

#### **SPECIFICATIONS**

**Type:** Acrylic styrene copolymer

**Appearance:** White liquid

Fragrance: Acrylic Viscosity: As water

**pH:** 8.7

Non-volatile %: 20.0

**Slip Resistance:** 0.5 min (ASTM D-2047) **Freeze-Thaw Stability:** Passes 3 cycles

**Dry Time:** 15-30 minutes

WHMIS: No TDG: No