MATERIAL SAFETY DATA SHEET (MSDS)



Spray Buff Maintainer

Cross-Link

Floor Finishes

SECTION I							
Product Name	Product Ty			WHMI			
Cross-Link	Spray Buff Maintainer D2					2B	
SECTION II HAZARDOUS INGREDIENTS							
Chemical Name				%	 	Toxicity	
d-limonene			Cas Registry No. 5989-27-5	3-7	LD500RAL(RAT) 4400 mg/kg		
Diethylene glycol ethyl ether			111-90-0	1-5	LD500RAL(RAT) 5500 g/kg		
	SICAL DATA	I			•- 1	• • • • • • • • •	
Appearance	Odour	pH	Boiling Point	Specific G			
White emulsion Scented 8.7 100 °C 1.0 100 %							
SECTION IV FIRE AND EXPLOSION HAZARD DATA							
Flash Point (°C): None Extinguising media: Not Applicable							
Special fire fighting procedures: None							
Unusual fire and explosion	Unusual fire and explosion hazards: None						
SECTION V > TOXI	COLOGICAL PROP	FRTIES					
			divity = 0				
HAZARD RATING: Health = 2 Flammability = 1 Reactivity = 0						Rating System	
Swallowing: Slightly Toxic. Inhalation: Not Applicable						0 = Insignificant	
I - Slight							
Skin Contact: Irritant 3 = High Eye Contact: Irritant 4 = Extrem							
Special Warning: None						4 = Extreme	
SECTION VI FIRST AID MEASURES							
Ingestion: Do not induce vomiting Drink 3-4 glasses of milk or water. Call a physician.							
Inhalation: Not Applicable							
Skin: Flush with water. If irritation persists, call a physician.							
Eyes: Flush with water for 15 minutes If irritation persists, call a physician.							
SECTION VII REACTIVITY DATA							
Stable: Yes							
Conditions to avoid: Sources of ignition							
Incompatibility with other materials: Strong oxidizing agents.							
Hazardous decomposition products: None							
Hazardous polymerization: Will not occur.							
SECTION VIII							
Hand protection: No							
Eve protection: No							
Ventilation: General							
Respiratory protection: No							
Other protective equipment: None							
Steps to be taken in case material is released or spilled: Mop up spillage. Rinse spill area with water and allow to dry.							
Waste disposal method: Flush with water into waste systems in accordance with municipal, provincial and federal regulations.							
Precautions to be taken in handling and storage: Normal handling processes. Inside storage at 4-40 °C recommended.							
Other precautions: Follow label use instructions.							
UN: Not Applicable TDG Class: None Packing Group: Not Applicable							
TDG Emergency Telephone Number: 613-996-6666 (COLLECT)							
SECTION IX	PERATION DATA						
Prepared by: M. Mikoluk	ENATION DAIA		l ast undate	ed: June 1, 201	5		
Location: Dustbane Products Limited, 25 Pickering Place, Ottawa, Ontario, K1G 5P4 – 613-745-6861							

Cross-Link Spray Buff Maintainer

"A spray buff solution used to repair your floor and maintain its high appearance between refinishing. Formulated to restore gloss to tired, worn floors while removing scuff marks and scratches."

FEATURES AND BENEFITS

Polymer technology: A.P.E. free., zinc free.

Easy application: Simply spray on and buff.

Easy recoating: Does not harm or damage floor for easy re-application of finish.

Slip resistant: Will not affect slip resistance of floor finish.

Maintains gloss level: Removes scratches and heel marks.

Natural citrus solvent: Cuts through black heel marks with ease.

WHERE TO USE

Use in heavy traffic areas such as hospital corridors, school classrooms, hallways, lobbies, supermarket aisles, malls, public office buildings and places where there is heavy foot traffic and where an outstanding appearance is desired.

HOW TO USE

Damp mop or auto scrub the floor with a neutral detergent. Spray buff whole areas using Cross-Link with a red pad. Do not let spray buff dry on the floor. Spray a light mist to avoid quick pad overload.

SPECIFICATIONS

Type: Emulsion

Appearance: White liquid

Fragrance: Citrus

Viscosity: As water

pH: 8.7

Slip Resistance: 0.5 min (ASTM D-2047)

Dry Time: N/A

WHMIS: Yes

TDG: No