



Safety Data Sheet

24 Hour Emergency Phone Numbers

Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-5053

1-352-323-3500

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

1. Identification

This Material Safety Data Sheet is available in American Spanish upon request.
Los Datos de Seguridad del Producto pueden obtenerse en Espanol si lo requiere.

Product Name:	Dynaflex 230 Clear	Revision Date:	6/19/2015
Product UPC Number:	74120	Supersedes Date:	9/7/2012
Product Use/Class:	Caulking Compound	SDS No:	00017001605
Manufacturer:	DAP Canada 475 Finchdene Square Unit 5 Scarborough, Ontario M1X 1B7 888-327-8477 (non - emergency matters)		
Preparer:	Regulatory Department		

2. Hazards Identification

EMERGENCY OVERVIEW: Under normal use conditions, this product is not expected to cause adverse health effects. This product contains ethylene glycol.

GHS Classification

Not a hazardous substance or mixture.

Symbol(s) of Product

None

Signal Word

Not a hazardous substance or mixture.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
White mineral oil	8042-47-5	10-25	GHS03-GHS07-GHS08	H270-304-312

Ethylene glycol	107-21-1	1.0-2.5 GHS03-GHS06	H270-331
Amorphous silica	112945-52-5	1.0-2.5 GHS03-GHS07	H270-315-319-332-335

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: No health hazards are known to exist. In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
White mineral oil	N.E.	N.E.	N.E.	N.E.
Ethylene glycol	N.E.	N.E.	N.E.	N.E.
Amorphous silica	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Appearance:	White (changes to clear as it cures)	Physical State:	Paste
Odor:	Very Slight Ammonia	Odor Threshold:	Not Established
Density, g/cm³:	1.04 - 1.04	pH:	Between 7.0 and 12.0
Freeze Point, °C:	Not Established	Viscosity (mPa.s):	Not Established
Solubility in Water:	Not Established	Partition Coeff., n-octanol/water:	Not Established
Decomposition Temperature, °C:	Not Established	Explosive Limits, %:	N.I. - N.I.
Boiling Range, °C:	N.I. - N.I.	Auto-Ignition Temperature, °C	Not Established
Minimum Flash Point, °C:	93.3	Vapor Pressure, mmHg:	No Information
Evaporation Rate:	Slower Than n-Butyl Acetate	Flash Method:	Seta Closed Cup
Vapor Density:	Heavier Than Air		
Combustibility:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion of ethylene glycol can cause gastrointestinal irritation, nausea, vomiting, diarrhea and if ingested in sufficient quantities, death.

CARCINOGENICITY: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
8042-47-5	White mineral oil	>5000 mg/kg Rat	2000 mg/kg Rabbit	>20 mg/L
107-21-1	Ethylene glycol	4000 mg/kg Rat	9530 mg/kg Rabbit	> 2.5 mg/L Rat
112945-52-5	Amorphous silica	>3300 mg/kg Rat	>2000 mg/kg Rabbit	>20 mg/L

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name:	Not Regulated.
DOT Technical Name:	N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethylene glycol	107-21-1

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

WARNING: This product contains chemicals known to the State of California to cause cancer.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

This product does not contain any chemicals known to the State of California to cause birth defects or other reproductive harm.

International Regulations: As follows -**CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class Consumer Commodity

16. Other Information

Revision Date: 6/19/2015 Supersedes Date: 9/7/2012
Reason for revision: HazCom2012/GHS Conversion
Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	1	Flammability:	0	Reactivity:	0	Personal Protection:	X
---------	---	---------------	---	-------------	---	----------------------	---

VOC Less Water Less Exempt Solvent, g/L:48.3

VOC Material, g/L:29

VOC as Defined by California Consumer Product Regulation, Wt/Wt%:0.1

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H270 May cause or intensify fire; oxidiser.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS03



GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.