Bona[®] Pro Series Hardwood Floor Refresher

Technical data sheet

Professional formula refresher provides a clear, highly durable gloss to polyurethane finished wood floors that are dull, worn, scratched, or shows signs of wear. This non-toxic, waterborne formula restores the beauty of wood floors, leaves no build-up, and is recoatable.

- Professional formula
- Specially formulated for use on hardwood floors
- Restores shine
- Easy application
- Urethane maintenance coating
- Dries in one hour
- Non-toxic
- Recoatable with finish
- GREENGUARD certified for indoor air quality

Technical data

Physical Characteristics:

Ingredients – Water, polymeric resins, Diethylene Gylcol Monoethyl Ether Color – Milky white (wet) pH – 8.0 Solids – 10 - 12% Density – 8.39 lbs./gallon (1.01 S.G.) Gloss Level – (60%)>80 Odor – Non-Offending Flash Point – None Stability – 2 year shelf life VOC – Does not exceed 2% Packaging – 1 quart plastic bottle

Application Characteristics:

Drying Time – 1 hour Application Tools – Bona[®] Microfiber Application Pad Coverage – 500 sq. ft. per quart Clarity – Clear when dry Leveling – Excellent Percent Cured After 24 hours – 90% Defoaming – Excellent Max. cure – 100% after 1 week

Recommended Use

- All types of unwaxed, residential and commercial polyurethane finished wood floors that are dull, worn, scratched, or show signs of wear
- Can be used on most "aluminum oxide" and "ceramic" type UV finishes

Directions

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET.

1. Remove furniture, rugs, etc. Vacuum, sweep or dust mop, then thoroughly clean with Bona Hardwood Floor Cleaner and the green Microfiber Cleaning Pad on your Bona Mop. Allow the floor to dry. 2. Gently rock product back and forth to mix. Slightly dampen the cream Microfiber Applicator Pad with water and attach to mop. Squirt product onto the floor and spread. Work in sections small enough to keep the Applicator Pad with water. 3. Allow to dry at least 1 hour before walking on the floor. For a glossier look, a second coat may be applied after 2 hours. Allow 24 hours before heavy foot traffic.

Maintenance

Clean-Up: Clean all tools and equipment with warm water.

Order Information

Item#: WT760051163 #/Case: 8

Rev 8/10 This data sheet replaces all previous versions





