


TAG

## Exposed Z6003AV Model For 3/4" Urinals



## **Flow Options**

D-EWS

0.5 Gallons Per Flush 1.0 Gal. Low Consumption

## Suffix Options (Check/Specify Appropriate Options)

- □-BG BioCare Handle
  □-D1 1" Supply
  □-H Handle on Front of Flush Valve
  □-L 1" [25] Metal Push Button
  □-L3 3" [76] Metal Push Button
  □-YJ Split Ring Pipe Support
  □-YK Solid Ring Pipe Support
- □- Other

**ENGINEERING SPECIFICATION:** ZURN Z6003AV AquaVantage<sup>®</sup> 'AV' Exposed Urinal Flush Valve- Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage<sup>®</sup> TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve is ADA compliant with a nonhold open and no leak handle feature, high back pressure vacuum breaker, one piece hex coupling nut, adjustable tailpiece, spud coupling and flange for top spud connection. Control stop has internal siphon-guard protection, vandal resistant stop cap, sweat solder kit, and a cast wall flange with set screw. Internal seals are made of chloramine resistant materials.

This space is for Architectural/engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

ZURN INDUSTRIES, LLC. ♦ COMMERCIAL BRASS OPERATION ♦ 5900 ELWIN BUCHANAN DRIVE ♦ SANFORD NC 27330 Phone: 1-800-997-3876 ♦ Fax: 919-775-3541 ♦ World Wide Web: www.zurn.com In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905-405-8272 Fax: 905-405-1292