



2064 146 Shown

PRODUCT FEATURES:

- **Self-Adjusting Sensor:** Sensor automatically sets the activation range on start-up by evaluating sink size and other factors. Will adjust range to adapt to changes in the bathroom environment.
- **Sensor in Spout Tip:** Clean, streamlined style. Hidden sensor reduces vandalism.
- **Self-Cleaning Solenoid Reduces Maintenance:** Integral wiper spring prevents clogging and run-on.
- **Easy to Service Integrated Strainer:** Patented in-line strainer protects the solenoid from debris. Strainer is enclosed in removable debris cup for easy service.
- **Safety Timer:** Helps prevent vandalism by turning off the faucet if the sensor is blocked for 55 seconds.
- **Power Options**
 - **PWRX™ Long-Life Battery System:**
Battery Life - 480,000 cycles (10 years @ 4,000 cycles per month). Advanced battery & electronics reduce the downtime and maintenance costs associated with changing batteries.
 - **DC CR-P2 lithium battery** will last for 200,000 uses (4 years @ 4,000 uses per month).
 - **Plug-In AC** - Includes UL Class 2 certified universal power supply with 6' cord.
 - **Hard-Wired AC** - Includes Class 2 UL certified universal Hard-Wired AC transformer.
 - **Multi-AC** - 1 power supply or transformer can run up to 15 faucets and/or flush valve.
- **Universal Voltage:** Plug-in and hard-wired power supply can accept input voltage range of 100 - 240 VAC, 50/60 Hz.
- **Lead-Free:** Faucet contains ≤0.25% total lead content by weighted average.
- **5-Year Limited Commercial Warranty**



MODEL NUMBER:

■ PWRX™ LONG-LIFE BATTERY POWERED

- **2064 146** 0.3 gpm PCA, VR multi-laminar spray
- **2064 145** 0.4 gpm PCA, VR multi-laminar spray.
- **2064 142** 1.25 gpm PCA, VR laminar flow outlet.

■ DC (CR-P2 lithium battery included)

- **2064 156** 0.3 gpm PCA, VR multi-laminar spray.
- **2064 155** 0.4 gpm PCA, VR multi-laminar spray.
- **2064 153** 1.25 gpm PCA, VR laminar flow outlet.

■ PLUG-IN AC (Power Supply included)

- **2064 166** 0.3 gpm PCA, VR multi-laminar spray.
- **2064 165** 0.4 gpm PCA, VR multi-laminar spray.
- **2064 162** 1.25 gpm PCA, VR laminar flow outlet.

■ HARD-WIRED AC (Transformer included, electrical box by others)

- **2064 196** 0.3 gpm PCA, VR multi-laminar spray.
- **2064 195** 0.4 gpm PCA, VR multi-laminar spray.
- **2064 192** 1.25 gpm PCA, VR laminar flow outlet.

■ MULTI AC (Extension cable & Y-connector included) - Must order transformer separately.

- **2064 176** 0.3 gpm PCA, VR multi-laminar spray.
- **2064 175** 0.4 gpm PCA, VR multi-laminar spray.
- **2064 172** 1.25 gpm PCA, VR laminar flow outlet.

■ OPTIONAL 4" (102mm) or 8" (203mm) Deck plates

- **605XTMV1070** Thermostatic mixing valve, 20" (508mm) long flexible stainless steel inlet hoses with 3/8" (10mm) compression fitting. ASSE 1070 certified down to 0.3 gpm.

*PCA - Pressure Compensating

GENERAL DESCRIPTION:

Deck-mount electronic faucet with proximity operation. Vandal-resistant brass construction with single-post mounting. Operates on DC (battery) or AC permanent power. Water pressure range from 20 - 120 psi. Single inlet. 18" (457 mm) flexible stainless steel inlet hose with 3/8" compression fitting for inlet to control box.

RECOMMENDED SPECIFICATION:

Electronic, sensor-operated proximity lavatory faucet shall feature vandal-resistant brass body with single-post mount design and single inlet. Shall also feature a low energy use electronically operated solenoid valve with an in-line strainer, and microprocessor controlled proximity sensors. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Model shall be American standard # 2064 1____.

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

- ANSI A117.1
- ASME A112.18.1
- CSA B 125
- NSF 372



MEETS THE AMERICANS WITH DISABILITIES ACT
GUIDELINES AND ANSI A117.1 REQUIREMENTS
FOR ACCESSIBLE AND USABLE BUILDING
FACILITIES-CHECK LOCAL CODES

Finishes:

Polished Chrome 002

PVD Satin Nickel 295

