



500 CFM/11.0 SONES @ 0.10" SP.

Dimensions

Overall bottom projection - 193/4" Height (less chimney) -91/4" Available widths: 30" & 36"

Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel.

Painted: 24 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

Motor

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz.

Lighting

Two - GU10 base, MR16, 50 watt halogen lights.

Ducting Options

Vertical ducting: 6" round duct adapter complete with back draft damper ensuring quiet operation.

Ductless: Requires charcoal filter (not included).

Blower Wheel

Dual inlet, electronically balanced polymeric centrifugal blower wheel, 53/4" width 59 paddles.

Mounting

Wall mounted. Install 24" to 36" from cooking surface.


Filters

Grease Filter: BCGF-01 (included).
Charcoal Filter: BCCF-02 (not included).


Available Finishes

Stainless Steel, White, and Black





30" or 36"



PROJECT							ARCHITECT		
LOCATION							ENGINEER		
CONTRACTOR							SUBMITTED BY DATE		
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS





Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048

Specifications subject to change without notice.

Updated 3-16