



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ¹ (Yes/No)	Case qty
MR11													
64244	LED/MR11/4W/30K/38/GU4/ND/STD	4	GU4	12	3 000	80	25 000	260	38	550	30	N	48
MR16													
64003	LED/MR16/5W/27K/38/STD	5	GU5.3	12	2 700	81	40 000	428	38	924	35	Y	24
64004	LED/MR16/5W/30K/38/STD	5	GU5.3	12	3 000	83	40 000	437	38	950	35	Y	24
64005	LED/MR16/5W/40K/38/STD	5	GU5.3	12	4 000	82	40 000	472	38	976	35	Y	24
64006	LED/MR16/5W/50K/38/STD	5	GU5.3	12	5 000	85	40 000	442	38	784	35	Y	24
62462	LED/MR16/6W/27K/25/STD	6	GU5.3	12	2 700	82	40 000	360	25	1 863	35	Y	24
62465	LED/MR16/6W/27K/38/STD	6	GU5.3	12	2 700	82	40 000	360	38	974	35	Y	24
62463	LED/MR16/6W/30K/25/STD	6	GU5.3	12	3 000	82	40 000	380	25	1 689	35	Y	24
62466	LED/MR16/6W/30K/38/STD	6	GU5.3	12	3 000	82	40 000	380	38	1 001	35	Y	24
62464	LED/MR16/6W/40K/25/STD	6	GU5.3	12	4 000	82	40 000	410	25	1 998	35	Y	24
62467	LED/MR16/6W/40K/38/STD	6	GU5.3	12	4 000	82	40 000	410	38	1 018	35	Y	24
64007	LED/MR16/6.5W/27K/38/STD	6.5	GU5.3	12	2 700	81	40 000	599	38	1 307	50	Y	24
64008	LED/MR16/6.5W/30K/38/STD	6.5	GU5.3	12	3 000	83	40 000	595	38	1 213	50	Y	24
64009	LED/MR16/6.5W/40K/38/STD	6.5	GU5.3	12	4 000	83	40 000	667	38	1 326	50	Y	24
64010	LED/MR16/6.5W/50K/38/STD	6.5	GU5.3	12	5 000	84	40 000	655	38	1 312	50	Y	24
63092	LED/MR16/7W/27K/25/STD	7	GU5.3	12	2 700	80	40 000	500	25	2 330	50	Y	24
63093	LED/MR16/7W/27K/38/STD	7	GU5.3	12	2 700	80	40 000	500	38	1 372	50	Y	24
63094	LED/MR16/7W/30K/25/STD	7	GU5.3	12	3 000	80	40 000	500	25	2 507	50	Y	24
63095	LED/MR16/7W/30K/38/STD	7	GU5.3	12	3 000	80	40 000	500	38	1 449	50	Y	24
63096	LED/MR16/7W/40K/25/STD	7	GU5.3	12	4 000	80	40 000	520	25	2 472	50	Y	24
63097	LED/MR16/7W/40K/38/STD	7	GU5.3	12	4 000	80	40 000	520	38	1 524	50	Y	24
63554	LED/MR16/7W/50K/38/STD	7	GU5.3	12	5 000	80	40 000	540	38	1 355	50	Y	24

Reflectors



MR16 - GU10



PAR16



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
MR16 - GU10													
63993	LED/GU10/5W/27K/38/STD	5	GU10	120	2 700	81	40 000	446	38	964	35	Y	24
63995	LED/GU10/5W/30K/38/STD	5	GU10	120	3 000	83	40 000	452	38	937	35	Y	24
63994	LED/GU10/5W/30K/38/STD/GRY	5	GU10	120	3 000	83	40 000	452	38	937	35	Y	24
63996	LED/GU10/5W/40K/38/STD	5	GU10	120	4 000	83	40 000	484	38	1 017	35	Y	24
63997	LED/GU10/5W/50K/38/STD	5	GU10	120	5000	84	40 000	488	38	1 024	35	Y	24
62468	LED/GU10/6W/27K/25/STD	6	GU10	120	2 700	82	40 000	360	25	1 749	50	Y	24
62471	LED/GU10/6W/27K/38/STD	6	GU10	120	2 700	82	40 000	340	38	929	50	Y	24
62469	LED/GU10/6W/30K/25/STD	6	GU10	120	3 000	82	40 000	380	25	1 918	50	Y	24
62472	LED/GU10/6W/30K/38/STD	6	GU10	120	3 000	82	40 000	380	38	1 045	50	Y	24
62775	LED/GU10/6W/30K/38/STD/GRY	6	GU10	120	3 000	82	40 000	380	38	1 045	50	Y	24
62470	LED/GU10/6W/40K/25/STD	6	GU10	120	4 000	82	40 000	410	25	1 793	50	Y	24
62473	LED/GU10/6W/40K/38/STD	6	GU10	120	4 000	82	40 000	410	38	1 035	50	Y	24
63998	LED/GU10/6.5W/27K/38/STD	6.5	GU10	120	2 700	81	40 000	569	38	1 195	50	Y	24
64000	LED/GU10/6.5W/30K/38/STD	6.5	GU10	120	3 000	82	40 000	582	38	1 242	50	Y	24
63999	LED/GU10/6.5W/30K/38/STD/GRY	6.5	GU10	120	3 000	82	40 000	582	38	1 242	50	Y	24
64001	LED/GU10/6.5W/40K/38/STD	6.5	GU10	120	4 000	83	40 000	635	38	1 298	50	Y	24
64002	LED/GU10/6.5W/50K/38/STD	6.5	GU10	120	5 000	84	40 000	633	38	1 322	50	Y	24
63085	LED/GU10/7W/27K/25/STD	7	GU10	120	2 700	80	40 000	500	25	2 270	50	Y	24
63086	LED/GU10/7W/27K/38/STD	7	GU10	120	2 700	80	40 000	500	38	1 329	50	Y	24
63087	LED/GU10/7W/30K/25/STD	7	GU10	120	3 000	80	40 000	500	25	2 344	50	Y	24
63089	LED/GU10/7W/30K/38/STD	7	GU10	120	3 000	80	40 000	500	38	1 325	50	Y	24
63088	LED/GU10/7W/30K/38/STD/GRY	7	GU10	120	3 000	80	40 000	500	38	1 325	50	Y	24
63090	LED/GU10/7W/40K/25/STD	7	GU10	120	4 000	80	40 000	520	25	2 192	50	Y	24
63091	LED/GU10/7W/40K/38/STD	7	GU10	120	4 000	80	40 000	520	38	1 367	50	Y	24
63555	LED/GU10/7W/50K/38/STD	7	GU10	120	5 000	80	40 000	540	38	1 378	50	Y	24
PAR16													
63986	LED/P16/5W/30K/38/STD	5	E26	120	3 000	83	40 000	452	38	937	35	Y	24
62786	LED/P16/6W/30K/38/STD	6	E26	120	3 000	80	40 000	380	38	630	35	Y	24
63990	LED/P16/6.5W/30K/38/STD	6.5	E26	120	3 000	82	40 000	582	38	1 242	50	Y	24
63991	LED/P16/6.5W/40K/38/STD	6.5	E26	120	4 000	83	40 000	635	38	1 298	50	Y	24



¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² Typical lumens +/- 10 %

³ For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com



PAR20



PAR30SN

Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
PAR20													
63051	LED/P20/7W/27K/25/STD	7	E26	120	2 700	90	40 000	470	25	1 370	50	Y	12
63950	LED/P20/7W/27K/25/STD	7	E26	120	2 700	92	40 000	509	25	936	50	Y	12
63052	LED/P20/7W/27K/40/STD	7	E26	120	2 700	90	40 000	500	40	1 000	50	Y	12
63951	LED/P20/7W/27K/40/STD	7	E26	120	2 700	92	40 000	509	40	936	50	Y	12
63053	LED/P20/7W/30K/25/STD	7	E26	120	3 000	90	40 000	480	25	1 373	50	Y	12
63952	LED/P20/7W/30K/25/STD	7	E26	120	3 000	93	40 000	502	25	918	50	Y	12
63054	LED/P20/7W/30K/25/STD/BLK	7	E26	120	3 000	90	40 000	480	25	1 373	50	Y	12
63953	LED/P20/7W/30K/25/STD/BLK	7	E26	120	3 000	93	40 000	502	25	918	50	Y	12
63055	LED/P20/7W/30K/25/STD/GRY	7	E26	120	3 000	90	40 000	480	25	1 373	50	Y	12
63954	LED/P20/7W/30K/25/STD/GRY	7	E26	120	3 000	93	40 000	502	25	918	50	Y	12
63056	LED/P20/7W/30K/40/STD	7	E26	120	3 000	90	40 000	480	40	1 069	50	Y	12
63955	LED/P20/7W/30K/40/STD	7	E26	120	3 000	93	40 000	502	40	918	50	Y	12
63057	LED/P20/7W/40K/25/STD	7	E26	120	4 000	90	40 000	510	25	1 486	50	Y	12
63956	LED/P20/7W/40K/25/STD	7	E26	120	4 000	94	40 000	551	25	1 077	50	Y	12
63058	LED/P20/7W/40K/40/STD	7	E26	120	4 000	90	40 000	510	40	1 029	50	Y	12
63957	LED/P20/7W/40K/40/STD	7	E26	120	4 000	94	40 000	551	40	1 077	50	Y	12
63958	LED/P20/7W/50K/25/STD	7	E26	120	5 000	95	40 000	523	25	1 027	50	Y	12
63556	LED/P20/7W/50K/40/STD	7	E26	120	5 000	90	40 000	525	40	1 062	50	Y	12
63959	LED/P20/7W/50K/40/STD	7	E26	120	5 000	95	40 000	523	40	1 027	50	Y	12
PAR30SN													
63065	LED/P30S/10W/27K/25/STD	10	E26	120	2 700	90	40 000	780	25	3 230	75	Y	6
63968	LED/P30S/10W/27K/25/STD	10	E26	120	2 700	92	40 000	849	25	1 476	75	Y	6
63066	LED/P30S/10W/27K/40/STD	10	E26	120	2 700	90	40 000	780	40	1 541	75	Y	6
63969	LED/P30S/10W/27K/40/STD	10	E26	120	2 700	92	40 000	849	40	1 476	75	Y	6
63067	LED/P30S/10W/30K/25/STD	10	E26	120	3 000	90	40 000	820	25	3 240	75	Y	6
63970	LED/P30S/10W/30K/25/STD	10	E26	120	3 000	94	40 000	830	25	1 505	75	Y	6
63068	LED/P30S/10W/30K/25/STD/BLK	10	E26	120	3 000	90	40 000	820	25	3 240	75	Y	6
63971	LED/P30S/10W/30K/25/STD/BLK	10	E26	120	3 000	94	40 000	830	25	1 505	75	Y	6
63069	LED/P30S/10W/30K/40/STD	10	E26	120	3 000	90	40 000	820	40	1 581	75	Y	6
63972	LED/P30S/10W/30K/40/STD	10	E26	120	3 000	94	40 000	830	40	1 505	75	Y	6
63070	LED/P30S/10W/40K/25/STD	10	E26	120	4 000	90	40 000	850	25	3 318	75	Y	6
63973	LED/P30S/10W/40K/25/STD	10	E26	120	4 000	94	40 000	904	25	1 648	75	Y	6
63071	LED/P30S/10W/40K/40/STD	10	E26	120	4 000	90	40 000	850	40	1 680	75	Y	6
63974	LED/P30S/10W/40K/40/STD	10	E26	120	4 000	94	40 000	904	40	1 648	75	Y	6
63975	LED/P30S/10W/50K/25/STD	10	E26	120	5 000	96	40 000	865	25	1 607	75	Y	6
63558	LED/P30S/10W/50K/40/STD	10	E26	120	5 000	90	40 000	870	40	1 753	75	Y	6
63976	LED/P30S/10W/50K/40/STD	10	E26	120	5 000	96	40 000	865	40	1 607	75	Y	6

Reflectors

STANDARD's LED reflector lamps offer exceptional thermal management and professional grade optics to ensure uniform beam pattern, long life and luminous effect while reducing energy consumption.

Concise binning process ensures colour consistency from lamp to lamp. Ideal for goods and materials sensitive to heat and UV emission.



PAR30LN

Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
PAR30LN													
63059	LED/P30L/10W/27K/25/STD	10	E26	120	2 700	90	40 000	780	25	3 453	75	Y	6
63960	LED/P30L/10W/27K/25/STD	10	E26	120	2 700	92	40 000	839	25	1 492	75	Y	6
63060	LED/P30L/10W/27K/40/STD	10	E26	120	2 700	90	40 000	780	40	1 452	75	Y	6
63961	LED/P30L/10W/27K/40/STD	10	E26	120	2 700	92	40 000	839	40	1 492	75	Y	6
63061	LED/P30L/10W/30K/25/STD	10	E26	120	3 000	90	40 000	820	25	3 368	75	Y	6
63962	LED/P30L/10W/30K/25/STD	10	E26	120	3 000	94	40 000	848	25	1 482	75	Y	6
63062	LED/P30L/10W/30K/40/STD	10	E26	120	3 000	90	40 000	820	40	1 575	75	Y	6
63963	LED/P30L/10W/30K/40/STD	10	E26	120	3 000	94	40 000	848	40	1 482	75	Y	6
63063	LED/P30L/10W/40K/25/STD	10	E26	120	4 000	90	40 000	850	25	3 410	75	Y	6
63964	LED/P30L/10W/40K/25/STD	10	E26	120	4 000	94	40 000	929	25	1 655	75	Y	6
63064	LED/P30L/10W/40K/40/STD	10	E26	120	4 000	90	40 000	850	40	1 590	75	Y	6
63965	LED/P30L/10W/40K/40/STD	10	E26	120	4 000	94	40 000	929	40	1 655	75	Y	6
63966	LED/P30L/10W/50K/25/STD	10	E26	120	5 000	96	40 000	861	25	1 481	75	Y	6
63557	LED/P30L/10W/50K/40/STD	10	E26	120	5 000	90	40 000	870	40	1 753	75	Y	6
63967	LED/P30L/10W/50K/40/STD	10	E26	120	5 000	96	40 000	861	40	1 481	75	Y	6



¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² Typical lumens +/- 10 %

³ For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
PAR38													
63072	LED/P38/15W/27K/25/STD	15	E26	120	2 700	90	40 000	980	25	5 403	100	Y	6
63977	LED/P38/15W/27K/25/STD	15	E26	120	2 700	92	40 000	1 138	25	1 953	100	Y	6
63073	LED/P38/15W/27K/40/STD	15	E26	120	2 700	90	40 000	980	40	2 164	100	Y	6
63978	LED/P38/15W/27K/40/STD	15	E26	120	2 700	92	40 000	1 138	40	1 953	100	Y	6
63074	LED/P38/15W/30K/25/STD	15	E26	120	3 000	90	40 000	1 050	25	5 378	100	Y	6
63979	LED/P38/15W/30K/25/STD	15	E26	120	3 000	94	40 000	1 115	25	1 815	100	Y	6
63075	LED/P38/15W/30K/40/STD	15	E26	120	3 000	90	40 000	1 050	40	2 119	100	Y	6
63980	LED/P38/15W/30K/40/STD	15	E26	120	3 000	94	40 000	1 115	40	1 815	100	Y	6
63076	LED/P38/15W/40K/25/STD	15	E26	120	4 000	90	40 000	1 100	25	5 540	100	Y	6
63981	LED/P38/15W/40K/25/STD	15	E26	120	4 000	94	40 000	1 215	25	1 989	100	Y	6
63077	LED/P38/15W/40K/40/STD	15	E26	120	4 000	90	40 000	1 100	40	2 263	100	Y	6
63982	LED/P38/15W/40K/40/STD	15	E26	120	4 000	94	40 000	1 215	40	1 989	100	Y	6
63983	LED/P38/15W/50K/25/STD	15	E26	120	5 000	96	40 000	1 172	25	1 913	100	Y	6
63559	LED/P38/15W/50K/40/STD	15	E26	120	5 000	90	40 000	1 150	40	1 397	100	Y	6
63984	LED/P38/15W/50K/40/STD	15	E26	120	5 000	96	40 000	1 172	40	1 913	100	Y	6
63078	LED/P38/17W/27K/25/STD	17	E26	120	2 700	90	40 000	1 150	25	5 969	120	Y	6
63079	LED/P38/17W/27K/40/STD	17	E26	120	2 700	90	40 000	1 150	40	2 523	120	Y	6
63080	LED/P38/17W/30K/25/STD	17	E26	120	3 000	90	40 000	1 200	25	5 969	120	Y	6
63081	LED/P38/17W/30K/40/STD	17	E26	120	3 000	90	40 000	1 200	40	2 449	120	Y	6
63082	LED/P38/17W/40K/25/STD	17	E26	120	4 000	90	40 000	1 220	25	5 969	120	Y	6
63083	LED/P38/17W/40K/40/STD	17	E26	120	4 000	90	40 000	1 220	40	2 615	120	Y	6
BR20													
63600	LED/BR20/8W/27K/STD	8	E26	120	2 700	80	25 000	500	120	133	45	Y	20
BR30													
63601	LED/BR30/9.5W/27K/STD	9.5	E26	120	2 700	81	25 000	650	120	218	65	Y	20
BR40													
63084	LED/BR40/17W/27K/STD	17	E26	120	2 700	80	40 000	1 100	100	401	85	Y	6



¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² Typical lumens +/- 10 %

³ For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com

Reflectors