
Technical Information Bulletin

Date:	
In hands date of project:	
Project name/Number:	
Name of distributor:	
Client #:	
Name of end user:	



COMPATIBLE DIMMER LIST

NTELV-600

H703PTUW, HCL453P

IPL06, 6674, DSM10-1LZ

DAL06P, SAL06P, SLC03P, AAL06

DVCL-153P, CTCL-153P, MACL-153P, AYCL-

253P, DVCL-253P, DVELV-300P, SELV-300P,

Legrand

Cooper

Leviton

Lutron

ORDERING INFORMATION

Order code: 63977

Description: LED/P38/15W/27K/25/STD

UPC: 69549639775

Case quantity: 6

PERFORMANCE DATA

PAR38 Shape: Base: E26 Wattage (W): 15 Lamp voltage (VAC): 120 Colour temperature (K)**: 2 700 Average life (L70 hours): 40 000 Initial lumens (lm)*: 1 138 Initial lumens per watt (lm/W): 76 CRI: 92 R9: 56 25 Beam angle: CBCP: 1 953

- 40 °C / - 40 °F to 40 °C / 104 °F Operating temperature range:

*Initial lumens range: +/- 10 %

Power factor:

**Typical colour temperature range: +/- 10 %

0.96



















CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock do not use where directly exposed to water or weather.
- · Not for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open no user serviceable parts inside.
- Added weight of the device may cause instability of a freestanding portable luminaire. Use in portable table lamps in which the distance from the bottom of the base to the top of the lamp holder does not exceed three (3) times the minimum base diameter.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights. • Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com

- Not recommend	ded for use with timers.	
• NOT recommend	aed for use with timers.	

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: Company:

Signature: Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



Date:

